

**2200 LUMENS**

**SVGA RESOLUTION**

**MULTI-PURPOSE**



B O X L I G H T

# CP-635i

The **BOXLIGHT CP-635i** is the economical choice for medium to large venues. The CP-635i is packed with **IMPRESSIVE FEATURES** that make conducting large audience seminars, training sessions and educational lectures a breeze. With a stellar **2200 ANSI LUMEN** rating, **MULTIPLE INPUTS**, zoom lens, and **SVGA** resolution, the CP-635i enables you to command your audience's attention every time. And with the whisper mode, you don't have to shout to be heard. **HDTV COMPATIBILITY** and **COMPONENT VIDEO INPUT** guarantee that your projected video images will be brilliant. Exceptional features, spectacular images and friendly controls make the CP-635i a **SMART INVESTMENT**.

19332 Powder Hill Place  
Poulsbo, Washington 98370  
800.762.5757  
360.779.7901  
[www.boxlight.com](http://www.boxlight.com)



BOXLIGHT and the BOXLIGHT logo are registered trademarks of BOXLIGHT Corporation. © Copyright BOXLIGHT Corporation, 2002. All other marks are the property of their respective owners. Specifications subject to change without notice. M1-CP-635i-5/02

B O X L I G H T

# CP-635i

p r o j e c t o r



- Perfect for fixed installations and medium to large venues.
- 2200 lumens.
- True SVGA resolution with compression to SXGA. HDTV compatibility.
- Digital keystone correction.
- Digital zoom imaging.
- Multiple inputs.
- Manual zoom lens.
- Remote control.
- Whisper Mode for ultra-quiet operation.
- All BOXLIGHT projectors feature the latest in technology and design.
- Lifetime 24/7 technical support.
- The fastest response time in the industry from our state-of-the-art service center.

**BOXLIGHT.**  
Presenting a Better Way

To contact BOXLIGHT:

Direct	800.762.5757
Rental	800.736.6954
Education	800.689.6676
Government	800.497.4009
International	360.779.7901
Toll Free FAX	888.353.4242
Internet	<a href="http://www.boxlight.com">www.boxlight.com</a>



<b>Resolution</b>	800 x 600 true SVGA, with compression for 1280 x 1024 SXGA	<b>Dimensions</b>	11.7"/29.8 cm (W) x 3.0"/7.6 cm (3.7"/9.5cm w/ feet) (H) x 8.97"/22.8 cm (D)
<b>Brightness</b>	2200 ANSI lumens	<b>Horiz. Scan Frequency</b>	31-80 kHz
<b>Lamp</b>	200 watt, UHB	<b>Vertical Refresh Rate</b>	56-120 Hz
<b>Display Type</b>	(3) 0.9 in/2.3 cm TFT polysilicon LCDs	<b>Projection Lens</b>	Manual zoom and focus, 1:1.3 zoom ratio, F/1.7-2.1, f=36.8-47.8 mm
<b>Contrast Ratio</b>	350:1	<b>Diagonal Image Size</b>	30-300 in / 76-760 cm
<b>Colors</b>	16.7 million	<b>Throw Distance</b>	4-51.5 ft / 1.2-15.7 m
<b>Aspect Ratio</b>	4:3, 16:9 compatible	<b>Keystone</b>	Digital adjustment of +/- 15 degrees
<b>Inputs</b>	Computer: (2)15 pin; Audio:(1) L/R RCA, (2)computer mini-jack Video: (1) RCA composite, (1) component (RCA type), (1) S-video	<b>Adjustments</b>	On-board and remote
<b>Outputs</b>	Computer: (1) 15 pin; Audio: (1) Stereo mini-jack; Control Port: RS-232 control and mouse operation; USB mouse control	<b>Power Supply</b>	100V-240V; 50/60 Hz
<b>Audible Noise</b>	34 dB in whisper mode	<b>Power Consumption</b>	310 watts
<b>Audio</b>	(2) built-in 1-watt speakers with audio loop-through	<b>Compatibility</b>	SXGA, XGA, SVGA, VGA, Mac
<b>Video</b>	NTSC, NTSC 4.43, PAL, PAL (BGDHI), PAL-M, PAL-N, PAL-60, SECAM	<b>Warranty</b>	Two-year parts and labor (120-day lamp warranty)
<b>HDTV/EDTV</b>	Compatibility: 1080i, 1035i, 720p, 575i, 480p, 480i	<b>Accessories Included</b>	Card-type remote control, VGA cable, PS/2 mouse cable, component video cable, soft carry case, US and European power cords
<b>Weight</b>	7.2 lb / 3.25 kg	<b>Optional Accessories</b>	Ceiling mount plate and suspension pole, ceiling round flush mount kit, various carry cases, audio/video cables, RF remote controls, Mac /VGA adapter
<b>FCC Rating</b>	Class B Certification		