

Microtek CX4 Digital Projector


Astounding brightness and quality for all of your large presentation needs

Be assured of spectacular presentations with the Microtek CX4 LCD multimedia projector. This is the ideal projector for large group events, whether for shareholder meetings, museum multi-media shows, or presentations in schools or church auditoriums. Your audience will appreciate the extremely realistic and dazzling images the CX4 provides with its high (1,024x768) XGA resolution and 2000 ANSI lumen brightness. With plug-and-pay connection, a full suite of connectivity options, intuitive remote and On-Screen-Display controls, this digital projector makes presenting your brightest ideas effortless.

- XGA native resolution, SXGA capable
- 400:1 contrast ratio
- Extensive computer and video connectivity
- Full-featured remote control with USB mouse capability
- Digital Keystone Correction
- Easily portable at 8 pounds
- 3 year warranty and support



MICROTEK







Optional Accessories

Replacement Lamp Unit

215-00-990043

Dual-compartment Soft Pullman Case for Projector & Laptop

580-03-990030

Microtek Lab, Inc.

www.microtek.com

© 2002 Microtek Lab, Inc. Microtek is a trademark of Microtek Lab, Inc. All other trademarks or registered trademarks are the property of their respective holders. Lamp brightness subject to change with usage.

Specifications and bundles subject to change without notice. Not responsible for typographical errors.

MLISS-CX4-0502

Microtek CX4 Digital Projector

Projection System Features

Native Resolution	1024 x 768 (XGA)
Max Resolution	1280 x 1024 (SXGA)
Display Type	0.9" Poly-Silicon LCD with Micro-Lens x3
Brightness (typical)	2000 ANSI lumens
Lamp	200 watt SHP
Lamp Life	2000 hours
Brightness Uniformity (typical)	>80%
Projection Lens	1:1.3 manual zoom and focus; F 1.73 - 2.17, f 37.8 - 49.2mm
Displayable Colors	24-bit; 16.7 million
Contrast Ratio	400:1
Aspect Ratio	4:3 (supports 16:9)
Projected Distance	4.9' - 49.2' (1.5m - 15.0m)
Screen Size (diagonal)	30" - 350" (0.76m - 8.89m)
Digital Keystone Correction	±15 degrees
Audio	built-in 2 watt RMS speaker x2
Security Lock	Kensington® MicroSaver Security System

Technical Specifications

Horizontal Scan Rate	15KHz - 91KHz
Vertical Refresh Rate	56Hz - 85Hz
Installation Options	front, front ceiling, rear, rear ceiling
Plug and Project	VESA [®] DDC 1/2B
Power Consumption	300W; 22W standby mode
Power Supply Voltage	universal 100 - 240V, 50/60Hz AC
Operating Temperature	41°F - 95°F (5°C - 35°C)
Dimensions (WxHxD)	12.6" x 4.5" x 10.2" (320mm x 114mm x 260mm)
Weight	8.5 lbs / 3.9 kg
Audible Noise	<40dB (nominal room condition)

Connectivity

Computer Inputs	DVI x1, D-sub HD 15-pin x1
Video Inputs	S-video x1, Component Video Input x1, RCA composite video x1
Audio Inputs	RCA x1, Stereo mini jack x1
Outputs	Stereo mini jack x1, D-sub HD 15-pin x1, USB x1, PS/2 x1
Video	NTSC, NTSC 4.43, PAL, SECAM, HDTV (1080i, 480p, 480i)

Included Accessories

Remote control with laser pointer (with 2 AAA batteries), lens cap, power cord, analog RGB 15pin mini D-sub cable, S-video cable, RCA composite video cable, stereo mini jack cable, RCA stereo cable, control cable, USB cable

Warranty and Support

Standard three year limited warranty, 90-day lamp warranty.

Three years technical support with dedicated line. www.support.microtek.com

