

Projects a brilliant picture, delivering sharp, crisp images every time.

For Education, Multimedia & Presentations

Be assured of spectacular presentations with the Microtek LCD MVP800x multimedia projector. This is the ideal projector for your needs, whether for a lecture in a school auditorium or at a major corporate meeting.

Your audience will appreciate the extremely realistic and dazzling images due to the $XGA1,024 \times 768$ true resolution with 24.7 million colors.

Added to this are dual 3-watt stereo speakers that provide clear, dramatic sounds much greater than typical mono speaker designs. The

1.3x zoom and focus allow presenters to create images from 30" to 127" (diagonal). Regardless of ambient lighting, the 650 ANSI lumens create tremendous brightness and clarity with or without lights. And with the wireless remote, which includes the built-in laser pointer, presenters are encouraged to move freely around the room maintaining control over the projector and remote mouse function.

With little more to do than plug it in and turn it on, the MVP800x was designed to be uncomplicated and easy to operate. Master your presentations; choose the Microtek MVP800x projector.





LCD	Type Color Lens	Three 1.3" polysilcon , stripe pixel, TFT active matrix 16.7 million Manual focus, manual zoom (1:1.3x)
DISPLAY	Size Lamp Brightness Contrast Ratio	30"-127" (measured diagonally) 120W UHB 650 ANSI lumens (type) 200:1 (type)
AUDIO	Speakers Power	2 built-in stereo speakers 3W x 2
INPUT SIGNAL	Video	S-Video, NTSC, PAL, SECAM
COMPATIBILITY	PC Mac®*	PC and compatibles (from VGA up to 1024x768 non-interlaced) Power Mac TM (up to 1280 x 1024)
CONNECTOR	Video S-Video Audio	RCA Standard S-Video Mini-stereo connector
POWER	Voltage	100 - 240 VAC 50-60Hz., autoranging, power loop-through
CONTROLS	Physical On screen Wireless Remote	Located on top of projector; lamp, input, mute, menu, enter, volume, channel up/down, Channel up/down, enter, volume, picture adjust, brightness, contrast, postion, tracking, tint (video/s-video), format (video/s-video), special effects, color, color temp, reset Lamp, input, mute, menu, enter, volume, channel up/down
OPERATING	Temperature	Operation: 5° to 35° C, 41° to 95° F Storage: -10° to 60° C, 14° to 140° F
CONDITION	Humidity	Operation: 20% to 80% Storage: 20% to 80%
DIMENSIONS	Physical	257mm (L) x 360mm (W) x 197mm (H) 10" (L) x 14" (W) x 8" (H)
WEIGHT	Net	6.7 kg (14.9 lbs)
REGULATIONS		Info NEEDED:TK
OTHER		DDC1, DDC2B
ACCESSORIES	Included Optional	Remote control with laser pointer and wireless mouse**, soft carring case and cables* Travel wheels (carrying case)
WARRANTY	- Pronui	2 Years parts and labor, 30 days on lamp

'Mac cable adapter included • "PC only • Copyright © 2000 Microtek Labs, Inc. • All rights reserved • Corporate names and trademarks stated herein are the property of their respective companies • Specifications subject to change without notice.



www.microtekusa.com keyword: Microtek

Microtek Lab, Inc.,

3715 Doolittle Drive, Redondo, Beach, CA 90278 Tel: 310-297-5000 Fax: 310-297-5050



True SXGA 1280 x 1024 compressed resolution

High resolution and 24.7 million colors give your presentations a professional level of color and image quality.

650 ANSI lumens

Allows projection of clear, bright images even in a well-lit room.

Wireless remote

Laser pointer, projector controls and remote mouse** function built in for highly effective presentations.

Zoom and focus adjustment for superior presentations

A 1.3x zoom and focus that allows for easy set-up and can accommodate a wide variety of room sizes without repositioning the projector.

Audio & video porting

Use the MVP800x to present to large groups by sending audio and video signals to external audio and video applications.



3 Watt built in stereo speakers

A professional multimedia experience can be achieved with these dual 3W stereo speakers.



COLORS c = 59**CMYK** y= 12 m= 32 PMS 207