₹ T C

Acer P1385W TCO





Brief Introduction

contrast of 20000:1 and a WXGA 1280 x 800 resolution. The manufacturer Acer specifies a lamp life of 10000 hours, which converts to over 13.7 years at 2 hours per day. The projector can illuminate a picture width of up to 575 cm with its 3200 Ansi lumens. In room light, however, the image width should ideally be less than 383 cm. The HDMI MHL (Mobile High-Definition Link) port allows 1080p / 60 Hz image mirroring (screen mirroring) to be transmitted from a smartphone while it is being charged via the connection at the same time. Even 1080P video signals and 3D are no problem for the projector. At 30 decibels, the projector is very quiet compared to other projectors. The projector was launched in 2015 and is no longer sold by the manufacturer. 1 x DC3 0,65" DLP Chip

The standard portable P1385W TCO 3D DLP projector from Acer has 3200 Ansi lumens, a

Display Type Ansi-Lumen

Contrast

Offset

Black Level

Video Modes

Application

Light Source

Light Life

WXGA 16/10 Ti Digital Light Processing Chip

3200 / 2560 im Eco Mode 20000:1 full on/off 0,1600 min. Lumen

WXGA 1280 x 800 Resolution 1.024.000 Pixel

UXGA 1600 x 1200 compressed

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 3D, EDTV 480p, 576p

Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom 3D Compatibility Frame Sequential (3D Ready) | 2D-zu-3D Video Converter

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

200W UHP Lamp

Articel Nr.: MC.JL511.001 4000 h. 10000 h. in eco Mode

9,52% / 0,04 € **Operating Costs**

Manual **Focus**

Zoom Manual 1,1

Objective F=2,56-2,80 f=21,00-23,10 mm

Throw Ratio 1,5-1,65:1

1 x 10W Audio

300 - 330 cm Lux:1280 Lux Room light max.: 256 Lux Candela pro m²:408 cd/m² 63 cm Foot-Lamberts:119 fL 16/10 screen width:200 cm Screen:1 Gain

2 x HDMI 1.4a mit MHL in 2 x D-sub 15pin in 1 x out

Cinch Video in Cinch Stereo in S-Video in

Mini Jack Audio in und out

Connections USB Typ B in

RS232C Din 9 pin in 5V Trigge rout



Ceiling Mounting

Power 252W

Size WxHxD 308 x 86 x 211 mm (12,1"x3,4"x8,3") 5,59 L/dm³

Operating Noise 30 / 26 dB in Eco Mode

Weight 2,20 kg / 4,85 lbs.

Keystone Vert.: +/-40° automatisch

Illumination 85%

Frequenz H-sync: 15-100 kHz

V-sync: 24-120 Hz

Foot-Lamberts 119 fL / max. 575 cm screen width

408 cd/m²

Real Full HD 3D

■ Full HD 1080P compatible

Eco Mode

Automatic and manual vertical keystone correction

■ 6-segment colour wheel

■ Digital zoom 2x

2015 Discontinued (EOL) // Last update of the data: 2023-09-20

Created: 2015-08-06 12:48:10











Key: 315 cm

Key: 189 cm



Data

Status

Features











Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.