

PH730 Projector

DLP Technology - Home Theatre

Incorporating the latest in DLP technology, the Acer PH730 projector offers widescreen aspect ratio for **Home cinema**.

Encased in a stylish and robust silver and white shell, this projector provides long term performance and mobility.

Why a PH730 Projector?

- Resolution WXGA (1,280 x 768), UXGA (1,600 x 1,024)
- Contrast Ratio 2500:1
- Brightness 2,300 ANSI Lumens
- Projection Distance 3.94' (1.2 m) to 34.07' (10.38 m)













PH730 Projector DLP Technology – Home Theatre

Features Specifications

Deschation	Notice IMVOA (4,000 v. 700) Company 700 - 11VOA (4,000 v. 4000)
Resolution	Native WXGA (1,280 x 768), Support 720p, UXGA (1,600 x 1200)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, XGA, VGA (resizing)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/1/L), HDTV (720p, 1080i), EDTV (480p, 576pp) SDTV (480i, 576i)
Aspect Ratio	16:9 (Native), 4:3
Contrast Ratio	2500:1
Displayable Colors	16.7 Million Colors
Brightness	1,200 ANSI Lumens (Standard), 960 ANSI Lumens (ECO)
Projection Lens	F/2.5 – 2.8, f = 22.5mm – 26.69mm, 1:1.2 Manual Zoom and Manual Focus
Projection Screen Size	29.2" (0.74mm) – 300" (7.62m)
Projection Distance	3.94" (1.2m) – 34.07" (10.38m)
Throw Ratio	57.8" @ 2m
Horizontal Scan Rate	31 – 100 kHz
Vertical Scan Rate	56 – 85Hz
Lamp Type	230 W NHS Lamp
Lamp Life	2000 Hours (Standard), 4000 Hours (ECO)
Keystone Correction	+/- 16 Degrees
Projection Mode	Front, Rear, Front Ceiling, Rear Ceiling
Audio	2 Internal Speaker's each with 3 watts Output
Weight	3.5kg
Dimensions	350 x 282 x 119 mm
IR Remote Control	Laser Pointer & PgUp/PgDn function
Power supply	AC input 100 to 240 V auto-switching power supply
	285W
Power Consumption	
Power Consumption Operating Temperature	5 – 35 Degrees