Aiptek ProjectorCam C25



contrast of 1000:1 and a VGA 640 x 360 resolution. The manufacturer specifies an LED service

life of 10,000 hours, which translates to over 6.8 years at 4 hours of use. On the market since







Brief Introduction Beta 2.5

> 2013, the model is no longer offered by the manufacturer Aiptek. 1 x DLP Chip VGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast **Black Level** Offset

Display Type

25 1000:1 full on/off 0,0250 min. Lumen

VGA 640 x 360 Resolution 230.400 Pixel Video Modes

Game-Portabel | Very portable, small-screen projections. Application Very narrow picture width and rooms with very little light. Light Source **RGB LED**

Light Life 10000 h. 0,00 € LED **Operating Costs**

Focus Manual

Zoom No Zoom

Objective

Throw Ratio

Audio

USB (USB 2.0) Connections **HDMI** Mini Ceiling Mounting Yes

Power

Size WxHxD 124 x 64 x 59 mm (4,9"x2,5"x2,3") 0,47 L/dm3

Operating Noise

Weight 0,310 kg / 0,68 lbs.

Keystone Illumination

Frequenz

Foot-Lamberts 1 fL / max. 44 cm screen width

3 cd/m²


Features

2013 Discontinued (EOL) // Last update of the data: 2023-08-04

Created: 2013-11-12 16:27:10

Status Data

ω8 Lux (bei 200 cm Screen) 0,008 min. Lumen



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.