Ampro 7000D



Display Type

LCD TFT Panel 4/3 Liquid Crystal Display

Ansi-Lumen

Contrast Black Level 1000

თ324 Lux (bei 203 cm Screen) ფ -ფ -

Offset Resolution

Video Modes

NTSC, PAL, SECAM

Stationär | Permanent installation in the training room and meeting room as well as the conference

Application

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

Focus

- Lamp

Operating Costs -

Manual

Zoom

Objective

Throw Ratio

Audio 3W Mono

1 RGB-analog (BNC/5)

1 Composite (BNC/1) 1 Y/C (Hosiden 4-Pol)

1 RS232C

Ceiling Mounting -Power

Connections

Size WxHxD Operating Noise -

Lux:324 Lux Room light max.:65 Lux Candela pro m²:103 cd/m² Foot-Lamberts:30 fL 4/3 screen width: 203 cm Screen:1 Gain

Weight Keystone Illumination

H-sync: 15-64 kHz Frequenz V-sync: 50-120 Hz

30 fL / max. 275 cm screen width Foot-Lamberts

103 cd/m²

Features

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details

Status Data



