AVANZA WU9





Brief Introduction Beta 2.5

The WU9 3D Laser DLP has 7200 Ansi-Lumen, a contrast of 10000:1 and a WUXGA 1920 x 1200 resolution. The manufacturer AVANZA specifies a service life of 20000 hours, which is over 13.7 years with a daily viewing time of 4 hours. The projector also offers a lens shift function that makes image adjustment childs play. An image width of up to 862 cm is possible as the projector has 7200 Ansi lumens. The projector can create rooms with residual light with a smaller image width, we recommend a maximum of 575 cm. Playing 1080P is also no problem for the projector. It was launched in 2015 and is no longer offered by the manufacturer AVANZA. 1 x 0,67" DLP Chip

∞3200 Lux (bei 200 cm Screen)

0 10000:1 full on/off
0,32 min. Lumen

Display Type

WUXGA 16/9 Ti Digital Light Processing Chip

7200

10000:1 full on/off 0,7200 min. Lumen

Vert.: +60% -20% Hori.: +/-10%

Resolution

Ansi-Lumen Contrast

Black Level

Lens shift

WUXGA 1920 x 1200 2.304.000 Pixel

Video Modes 3D Compatibility Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p EDTV 480p, 576p

Frame Sequential (3D Ready)

Stationary | Permanent installation in the training room and meeting room as well as the conference room.

Very large screen width and rooms with plenty of light and shaded daylight.

Light Source Light Life

Application

Laser 20000 h.

Operating Costs

0,00 € Laser

Powered

Zoom

Focus

Powered

Objective

optional

Throw Ratio

Connections

optional

Audio

HDMI in

2 x D-sub 15pin in Cinch Video in S-Video in

RS232C Din 9 pin in

RJ45 in Yes

Ceiling Mounting

Lux:3200 Lux Room light max.:640 Lux Candela pro m²:1018 cd/m² 68 cm Foot-Lamberts:297 fL 16/9 screen width:200 cm Screen:1 Gain

Power 800W

Size WxHxD 551 x 290 x 430 mm (21,7"x11,4"x16,9") 68,71 L/dm³

Operating Noise 45dB

Weight 28,00 kg / 61,73 lbs.

Keystone - Illumination 90%

Frequenz Range max.: 165 MHz

Foot-Lamberts 297 fL / max. 862 cm screen width

1018 cd/m²

■ Full HD 1080P compatible

■ 24/7 continuous operation capable

■ Lan network compatible.

■ Lens shift Funktion

Optional Lenses

Name	Ratio	Distance	Shift V	Shift H	Zoom
		Zoom Optional Len	ses		
AP-HLA37	3.67-6.98:1	7.3-14 m	60-20%	+/-10%	
AP-HLA20	1.94-3.67:1	3.9-7.3 m	60-20%	+/-10%	Powered
AP-HLA15	1.45-1.94:1	2.9-3.9 m	60-20%	+/-10%	Powered
AP-HLA12	1.21-1.45:1	2.4-2.9 m	60-20%	+/-10%	Powered
		Fix Optional Lense	es		
AP-HLA07	0.77:1	1.5 m	0.00% Fix		No Zoom
Status	2015 Discontinued (EOL) // Last update of the data: 2023-08-04				

Data

Features





More Details





Shift: 68 cm

Shift: 23 cm

Shift: 20 cm

Shift: 20 cm

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.