

MULTI PROJECTOR

MP-15E



Focus on the presentation and not the peripherals

- Change between five media sources without changing your equipment.
- Zoom in on solid objects, transparencies, or PC images.
- Vary your projected image from 25 to 252 inches and make easy keystone corrections to suit audiences of any size.
- Add sound to your presentation with built-in 1.5 x 1.5 watt stereo speakers.
- Simple one-touch operation lets you concentrate on the project and not the projector.

Five display options in one package

- Documents & Photographs
- 3D Solid Objects
- Data (PC / Mac Images)
- Video (RCA / S-VHS / DVD)
- Transparencies

Built-in laser pointer Remote controller

Simple input and adjustment of various functions including:

- Document Rotation
- Freeze
- Zoom and Scroll
- Keystone Correction



MP-15E Specifications

Panel Type		0.9-inch TFT LCD x 3 pieces, aspect ratio 4:3
Resolution		XGA (1,024 x 768)
PC Compatibility		VGA to SXGA
Projection Lens		Manual zoom (1 – 1.2 times) f:36-43.2mm F:2.3-2.6
Light Source		150W super-high-pressure mercury lamp
Screen Size		Min. 25 inches – Max. 252 inches (projection distance 1.15m – 10m)
Color Reproducibility		Full color (16.77 million colors)
Light Output/Center to Edge		1,100 ANSI lumens/85%
Contrast Ratio		400:1
Sound Output		1.5W x 1.5W stereo speakers
Compatible Scanning Frequency	Horizontal	15 – 80KHz
	Vertical	50 – 75Hz
Keystone Correction		+/- 15 degree adjustable
Analog RGB Input/Output	Input Terminal (Image)	Mini D-sub 15 pins x 1
	Input/Output Terminal (Sound)	Stereo mini-jack x 1
	Output Terminal (Image)	Mini D-sub 15 pins x 1
	Zoom	4X zoom
Video Input/Output	Input Signal Type	NTSC, PAL, SECAM, Y/C
	Input Terminal (Image)	RCA pin x 1, S-Video terminal (Mini DIN 4 pins x 1)
	Input Terminal (Sound)	RCA pin (L/R) x 1
Operational Environment		Temperature 0 – 35°C, humidity 20 – 80% (no condensation)
Input Power		100-120 VAC / 220-240 VAC
Power Consumption		250W
External Dimensions		298(W) x 398(D) x 190(H)mm excluding projected section
Weight		5.4kg (approx. 12 lbs.)
Standard Accessories		Power cable (3m), personal computer interface cable, (2m, Mini D-sub 15 pins), remote controller, lens cover, instruction manual, batteries (AA x 2),
Document Camera		1/2-inch color CCD 2,000,000 pixels
		4 frames/second scan speed
Resolution		760 TV lines (horizontal resolution)



NIPPON AVIONICS CO.,LTD.

Overseas Department

20-1, Nishi-Shinbashi 3-chome, Minato-ku Tokyo 105-0003, Japan

Phone: 81-3-5401-7386 Fax: 81-3-5401-7344

URL <http://www.avio.co.jp/>

Printed in Japan