## Barco RD 701sOEM 67"(120V)

Display Type

7" CRT Liquid gekoppelt

Ansi-Lumen

ω48 Lux (bei 200 cm Screen) c -e -

Contrast Black Level

Offset

Resolution

Video Modes

NTSC, PAL, SECAM Pal 60 NTSC 4,43

Application

CRT Projection | Very narrow picture width and rooms with very little light.

Light Source CRT Röhre

Light Life

ca. 10000 - 20000 h. (je nach Anwendung)

**Operating Costs** 

**Focus** 

Manual

Zoom

kein zoom

Objective

HD214

Throw Ratio

Audio

Connections

Ceiling Mounting Yes 300W Power

Size WxHxD Operating Noise -

Lux:48 Lux Room light max.:10 Lux Candela pro m<sup>2</sup>:14 cd/m<sup>2</sup> Foot-Lamberts:4 fL 4/3 screen width:200 cm Screen:1 Gain

Weight Keystone Illumination

H-sync: 15-50 kHz V-sync: 37-155 Hz

Range max.: 45 MHz

Foot-Lamberts

Frequenz

4 fL / max. 105 cm screen width

14 cd/m<sup>2</sup>

■ Digital convergence setting

■ 32 memory locations

Status

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details

Data

**Features** 





https://www.projector-database.com/pro/barcoRD701sOEM67120V-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.