Barco RD 801S - 67"

8"CRTLiquid coupled Projection system

o 10 Lux (with 200 cm canvas) Ansi-Lumen

Contrast Black value

Offset Resolution

Playback signals NTSC, PAL, SECAM Pal 60 NTSC 4,43

CRT stationary | | Permanent installation in the training room and meeting room as well as

conference room. Area of application

Very small image width and rooms with very little room light.

Light source CRT tube

Light lifetime approx. 10000 - 20000 hours (depending on the application)

Operating costs

The focus Manual

Zoom no zoom

Objective HD 114

Projection ratio

Audio

Connections Ceiling mounting Yes 450W Electricity consumption **Dimensions BxHxT**

Operating noise

Weight 296,00 kg / 652,57 lbs.

Keystone correction illumination

H-sync: 15-65 kHz

V-sync: 37-155 Hz frequency

Max. bandwidth: 70 MHz

1 fL / max. 48 cm image width Foot-Lamberts

Candela per m2 3.5 cd/m2

■Digital convergence setting ■Housing color: grey ■38 memory spaces Equipment (extras)


Screen Mirroring

Year of construction - // Last data change: 2023-08-04

More details



Due to our constant commitment to the continuous improvement of the quality of our projector database, this brochure can be subjected to change even without prior notice. HCinema is not liable for any errors or omissions contained in the product descriptions.



4/3 Screen width: 200 cm

.Screen:1 Gain