
BARCO S 4 0 - 4

Barco FS40-4k





Brief Introduction Beta 2.5

> 1 x DLP Chip WQXGA 4/3 Ti Digital Light Processing Chip

by the projector. The model built in 2019 is no longer offered by Barco.

Display Type

3000 Ansi-Lumen 1800:1 full on/off Contrast Black Level Offset

1,6667 min. Lumen

 ω 1000 Lux (bei 200 cm Screen)
 α
 1800:1 full on/off
 0,556 min. Lumen

Resolution

WQXGA 2560 x 1600 4.096.000 Pixel

UHD (4K2K+) 3840 x 2400 compressed

Video Modes

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD (komprimiert), 3D, EDTV 480p, 576p Frame-Packing (Full HD 3D) | Side-by-Side | Top-and-Bottom

Frame Sequential (3D Ready)

3D Compatibility

Stationary | Permanent installation in the training room and meeting room as well as the

which is over 34.2 years with a daily viewing time of 4 hours. The projector will be able to

illuminate a picture width of 477 cm well. However, if room light is available, the picture width

should ideally not exceed 318 cm. Furthermore, it is Full HD 1080P and 4K (compressed) as well as 3D compatible, and therefore all currently available Blu-ray formats can be recognized

conference room.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source Light Life

Application

LED 50000 h.

Operating Costs

0,00 € LED

Focus

Powered

Zoom

Powered

Objective

optional


Throw Ratio

optional

Audio

2x DP1.2 Connections

2x Dual-Link DVI-I HDBaseT erweiterbar HDMI2.0 erweiterbar **RJ 45 Ethernet RS232** in 2x USB



Ceiling Mounting Power

Size WxHxD 450 x 244 x 457 mm (17,7"x9,6"x18") 50,18 L/dm³

12 V Ausgang

Yes

500W

Operating Noise 33dB

Weight 21,50 kg / 47,4 lbs.

Keystone -Illumination -

Frequenz -

Foot-Lamberts 93 fL / max. 477 cm screen width

319 cd/m²

Real Full HD 3D

■ Full HD 1080P compatible

Features Warping

■ 360° installable

■ Lan network compatible.

original R9802232

Object lens original R9801230 / EN43
Object lens original R9801221 / EN46
Object lens original R9801216 / EN41

Object lens original R9801211 / EN44

Order here: https://www.hcinema.de/lampen/shop-en.php?id=hc36930

Optional Lenses

Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses				
1.12-1.58:1	2.2-3.2 m			Powered
0.75-1.13:1	1.5-2.3 m			Powered
0.8-1.21:1	1.6-2.4 m			Powered
1.58-2.33:1	3.2-4.7 m			Powered
2.5-4.6:1	5-9.2 m			Powered
Fix Optional Lenses				
0.28:1	0.6 m			No Zoom
0.61:1	1.2 m			No Zoom
0.75:1	1.5 m			No Zoom
	Zoom O 1.12-1.58:1 0.75-1.13:1 0.8-1.21:1 1.58-2.33:1 2.5-4.6:1 Fix Op 0.28:1 0.61:1	Zoom Optional Lenses 1.12-1.58:1 2.2-3.2 m 0.75-1.13:1 1.5-2.3 m 0.8-1.21:1 1.6-2.4 m 1.58-2.33:1 3.2-4.7 m 2.5-4.6:1 5-9.2 m Fix Optional Lenses 0.28:1 0.6 m 0.61:1 1.2 m	Zoom Optional Lenses 1.12-1.58:1 2.2-3.2 m 0.75-1.13:1 1.5-2.3 m 0.8-1.21:1 1.6-2.4 m 1.58-2.33:1 3.2-4.7 m 2.5-4.6:1 5-9.2 m Fix Optional Lenses 0.28:1 0.6 m 0.61:1 1.2 m	Zoom Optional Lenses 1.12-1.58:1

2019 Discontinued (EOL) // Last update of the data: 2023-08-04

Created: 2020-01-05 19:47:45

More Details

Status

Data

Optional





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.