## Digital Projector

## **PB9200**

Presentation Pro



## **Key Features**

- 17 lbs
- Motorized Zoom, Motorized Focus, Motorized Lens shift (10:1 to 1:1)
- LCD Projection System (0.99" TFT x 3)
- 4500 ANSI Lumens
- Native XGA Resolution
- 800:1 Contrast Ratio
- · 4 Optional Interchangeable Lens
- 2-Way Digital Keystone (Horizontal/Vertical)

## **Specifications**

opecifications		
Projection System	Polysilicon active-matrix TFT LCD	
Panel	0.99" P-Si TFT LCD (with Micro Lens) x 3	
Native Resolution	XGA(1024x768)	
Resolution Supported	640x350 to 1280x1024	
Brightness	4500 ANSI lumens (80% at economic mode)	
Contrast Ratio	800:1	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Lens	F=1,7 to 2.4, f=31 ~ 46mm	
Zoom Ratio	Motorized Zoom, 1:1.5	
Image Size (Diagonal)	40" to 500"	
Throw Ratio	100" @ 9.8 feet (100" @ 3m)	
Lamp	310W, 1500 hours (2000 hours at economic mode)	
HDTV Compatibility	480p, 576p, 720p, 1080i	
Video Compatibility	NTSC, NTSC 4.43, PAL(BGDHI), SECAM, PAL-M, PAL-N, PAI	
Horizontal Frequency	15~91 kHz	
Vertical Scan Rate	50 ~ 120 Hz	
Input Terminals	PC- Analog RGB: D-sub	15 pin x 1
	PC PC- Analog RGB: BNC x	5(share component video)
	Digital RGB: M1-D(HDCP)	
	Audio: Stereo Mini Jack	x 2 (RGB use)
	S-Video: Mini Din 4 pin x	
	Composite Video: RCA x 1	
	A/V Component Video: RCA x 3, BNC x 3 (share RGB)	
	Audio: RCA x 2 (Video Use)	
Output Terminals	Analog RGB: D-Sub 15 pin x 1	
	Audio - Stereo mini jack x 1	
	Audio - 1 Watt Speaker x 2	
Control Terminals	RS232 (Serial): 9 pin D-sub x 1	
	USB mouse control: via M1-D terminal	
	Wired remote control: Stereo-mini jack x 1	
	Wireless DC Jack: Voltage Classification 2 x 1 (5V/1A)	
Dimensions (W x H x D)	16.5 x 6.3 x 12.6 inches (419x160x320 cm)	
Weight	17 lbs; 7.7kgs	
Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	470W (Max., 80% at Economic mode)	
Audible Noise		
	<39/34 dB (Normal/Economic mode)	
On-Screen Display	English/French/German/Italian/Spanish/Norwegian/Dutch/	
languages	Portuguese/Korean/Simplified Chinese/Russian/Japanese/ Swedish/Finnish/Polish	
Features		E. District Process
	Digital Keystone	4x Digital Zoom
	(+/- 15° Vertical correction;	Customized start-up screen
	+/- 5° Horizontal correction)	Vertical lens shift
	Easily replaceable lenses	Network function
	Progressive scan	PIP
	Picture Freeze by Remote control	
	or RS-232 function	HDCP Decoding
	Blank Function	Digital Gamma Correction
Accessories (Standard)	User's Manual	RGB Cable
	Safety Manual	RCA Video/Audio Cable
	Remote Control	M1 Cable (DVI/USB to M1)
	AA Batteries	PWR Cord (US, EU, UK)
Accessories (Optional)	Ceiling Mounting Kit	Mac Adapter
	Lamp Module	Optional Lens
	Air Filter	Wireless Pro



