

**Brief Introduction** Beta 2.5

Display Type

Ansi-Lumen Contrast Black Level

Offset

Resolution Video Modes

Application

Light Source

Light Life

**Operating Costs** 

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

The Boxlight model ProColor 2101 is an LCD projector with VGA 640 x 480 resolution and a contrast of 100:1. The projector can illuminate images up to 151 cm wide thanks to its 300 Ansi lumens. In room light, however, the image width should ideally be less than 101 cm. The projector is no longer sold by the manufacturer.

ก 100:1 full on/off ปี 1 min. Lumen

ω97 Lux (bei 203 cm Screen)

LCD TFT Panel

VGA 4/3 Liquid Crystal Display

300 100:1 full on/off 3,0000 min. Lumen

VGA 640 x 480 307.200 Pixel

NTSC, PAL, SECAM

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Very narrow picture width and rooms with very little light.

- Lamp

Articel Nr.: Lamp-so4386

Manual

2 x S-Video: (1) Mini DIN 4-pin

2 x Video: (1) RCA jack 4 x Cinch Stereo in 1 x out

Serial Port D-sub 15pin Microphone in Computer in




Ceiling Mounting Power Size WxHxD **Operating Noise** 

9,00 kg / 19,84 lbs.

Keystone Illumination

Weight

Frequenz



Foot-Lamberts 9 fL / max. 151 cm screen width

31 cd/m<sup>2</sup>

Features

Freeze

Status Data

■ Keystone correction timer, freeze frame (),- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details



https://www.projector-database.com/pro/boxlightprocolor2101-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.