

Seattle X35N

Specifications



BRIGHTNESS

3500 Lumens (Standard)

2300 Lumens (Economy)

RESOLUTION

1024x768 XGA (Native)

1600x1200 UXGA (Compatible)

DISPLAY TYPE

0.63" LCD w/ MLA x 3

CONTRAST RATIO

500 :1

ASPECT RATIO

4:3 Native

16:9 Compatible

THROW RATIO

1.45 ~ 1.73 (x screen width)

PROJECTION LENS

Manual Zoom & Focus

ZOOM RATIO

1.2:1

DIAGONAL IMAGE SIZE

40" - 300"

THROW DISTANCE

3.33' - 25' Feet

KEystone

+/- 30° Vertical

LAMP

230 watt UHP

LAMP LIFE

2000 (Standard)

3000 (Economy)

INPUTS

VGA

DVI-I

S-Video

Composite

Component

Audio x 2 (3.5mm)

OUTPUTS

VGA

Audio (3.5mm)

PROJECTOR CONTROLS

USB

RS232 (9-pin)

RJ45 LAN Connection

COMPATIBILITY

VGA, SVGA, XGA, SXGA, UXGA, Mac

EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

FCC CERTIFICATION

FCC-B, UL, cUL, TUV, CD, CE, CCC

VIDEO COMPATIBILITY

NTSC, NTSC 4.43, PAL M/N 60, SECAM

AUDIO

1 x 8w Mono Speaker

DECIBEL RATING

33 dB (standard) / 30 dB (economy)

H-REFRESH RATE

31-92 kHz

V-REFRESH RATE

48-120 Hz

POWER SUPPLY

AC 100 ~ 240 Volts

50-60Hz (auto ranging)

POWER CONSUMPTION

310 Watts (standard)

<5w standby

DIMENSIONS (WxDxH)

12.8" x 10.24" x 3.8" Inches

WEIGHT

7.3 Lbs

WARRANTY

3 year parts & labor / 90 day lamp

Special features of the Seattle X35N include:

LAN Connectivity—For network installation. Manage your projectors through a web-based platform.

Quick Start Up and Shut Down—Start presenting quickly and only a 10 second cool down cycle when you finish!

Side Changing Lamp and Filter—Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.

Throw Distance (ft)

