SoundView

BRIGHTNESS
3000 Normal Mode
2700 Eco Mode
RESOLUTION
1024 x 768 XGA native
1280 x 1024 SXGA compressed
DISPLAY TYPE
TI DLP 0.7 inch DMD 12° DDR
CONTRAST RATIO
1000:1
ASPECT RATIO
Native 4:3
Compatable 16:9, 1:1
LAMP
Osram VIP 250w
LAMP LIFE
2000 hours (normal Mode)
3500 hours (eco Mode)
DIAGONAL IMAGE SIZE
40"-120" inches
1-3 meters

*Special features of the **SoundView** include:*

***Stereo Sound**—The first and only projector in the industry with built in stereo sound—4 on-board speaks and a subwoofer are sure to sound great!*
***Multiple inputs**—Connect to multiple peripheral systems at the same time.*

OPTIONAL ACCESSORIES:
Extended Warranty
Cable: Audio / DVI-VGA / Component / Composite Video
Universal Ceiling Mount / Suspension Pole/ Round Flush Kit
Spare Lamp Module

SHIPS WITH:
Remote Control
User Manual/CD ROM
Power Cord / Soft Carry Case
Audio Video Cable / PC Audio Cable (mini jack)
DVI/VGA Cable

PROJECTION LENS
Manual Zoom/Focus
THROW DISTANCE
4'-16' feet
1.38-5 meters
THROW RATIO
1.7-2.0 (x screen width)
INPUTS
Composite Video
Component Video
S-video
DVI-I
OUTPUTS
Computer Out
Audio Out (mini jack)
COMPATIBILITY
VGA, SVGA, XGA, SXGA
CONTROLS
RS232 Port
KEYSTONE
Vertical +/- 12°

VIDEO
NTSC, PAL, SECAM
HDTV / EDTV / SDTV
480i/p, 576i/p, 720p, 1080i
AUDIO
4 x 15w speakers
1 x 5w subwoofer
(built-in amplifier)
DIMENSIONS (WxDxH)
13.1 x 11.6 x 4.84 inches
33.3 x 29.5 x 12.3 cm
WEIGHT
10.49 lbs / 4.76 kg
DECIBEL RATING
37dB (normal) / 34dB (eco)
WARRANTY
2 year parts & labor
(120 day/500 hour lamp life guarantee)
FCC CERTIFICATION
Class B

H-SCAN FREQUENCY
15-82 Hz
V-REFRESH RATE
50-85 Hz
POWER SUPPLY
100V /240V 50/60Hz
PWR. CONSUMPTION
345w

BOXLIGHT® CORPORATION
19302 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct 800.762.5757
International 360.779.7901
Partners 866.688.3636

© 2007 BOXLIGHT Corporation. All rights reserved. Specifications are subject to change without notice.