





Brief Introduction

Beta 2.5

A brief introduction to the Casio XJ S39. The standard portable DLP projector has an XGA 1024 x 768 resolution and a contrast of 1800:1. As the projector has horizontal and vertical keystone correction, the projector can be set up with plenty of free space in the room. A picture width of up to 435 cm is possible. However, the image should be smaller in room lighting. We recommend max. 290 cm. The model built in 2009 is no longer offered by Casio.

Display Type

1 x 0,55" DLP Chip

XGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level Offset

2500

1800:1 full on/off 1,3889 min. Lumen ω833 Lux (bei 200 cm Screen)

ิ 1800:1 full on/off 0,464 min. Lumen

Resolution

Video Modes

XGA 1024 x 768 786.432 Pixel

presentations.

210W Lamp

UXGA 1600 x 1200 compressed

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Application

Medium screen width or rooms with little light, max. 100 lumens.

Light Source

Light Life

Operating Costs

Powered Focus

Powered 2 Zoom

Objective

Throw Ratio 1.4-2.8:1

Audio 1W Mono

> D-Sub 15 pin in AV Video in USB Typ A **RS232C**

Ceiling Mounting

Connections

Yes Power

270 / 220W in Eco Mode

270 x 43 x 199 mm (10,6"x1,7"x7,8") 2,31 L/dm3 Size WxHxD

Operating Noise

1,80 kg / 3,97 lbs. Weight

Vert.: +/-30° automatisch Keystone

Hori.: +/-30°


Illumination

H-sync: 31-68 kHz Frequenz V-sync: 56-85 Hz

77 fL / max. 435 cm screen width Foot-Lamberts

264 cd/m²

Lux:833 Lux Room light max.:167 Lux Candela pro m²:264 cd/m² 75 cm Foot-Lamberts:77 fL 4/3 screen width:200 cm Screen:1 Gain



280 - 560 cm

Freeze ■ Eco Mode

■ Automatic and manual vertical keystone correction

■ Kensington Slot

■ Password protection

■ 2x digital zoom,

2009 Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

More Details

Features





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.