ChiStar CX 690





Brief Introduction

Beta 2.5

Display Type

Ansi-Lumen Contrast

Black Level Offset

Resolution

Video Modes

Application

Light Source Light Life

Operating Costs

Focus

Objective

Zoom

Throw Ratio

Audio

Connections

Ceiling Mounting Power

Size WxHxD **Operating Noise**

Weight Keystone

Illumination

Frequenz Range max.: 230 MHz

Foot-Lamberts

A brief introduction to the ChiStar CX 690. The LCD projector has an XGA 1024 x 768 resolution and a contrast of 500:1. An image width of up to 493 cm is possible, as the projector has 3200 Ansi lumens. However, if room light is available, the picture should be max. 329 cm wide. The projector is no longer sold by the manufacturer.

3 x LCD TFT Panel

XGA 4/3 Liquid Crystal Display

3200 500:1 full on/off 6,4000 min. Lumen

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

PAL, SECAM, NTSC

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

250W Lamp 2000 h.

Manual

Manual

D-sub 15pin in und out Cinch Video in

S-Video in Mini Jack **USB**

RS232C Yes 340W

350 x 120 x 270 mm (13,8"x4,7"x10,6") 11,34 L/dm³

Lux:1067 Lux Room light max.:213 Lux Candela pro m²:339 cd/m² Foot-Lamberts:99 fL 4/3 screen width:200 cm Screen:1 Gain

4,50 kg / 9,92 lbs. Vertical

95%

H-sync: 15-126 kHz V-sync: 43-200 Hz

99 fL / max. 493 cm screen width

339 cd/m²

Features Status Data

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.