Chuangrong 103 HT







Brief Introduction

Beta 2.5

width of 87 cm well. However, if room light is available, the picture width should ideally not exceed 58 cm. At just 25 decibels, the device is one of the quieter projectors. The model is no longer offered by Chuangrong. 1 x LCD TFT Panel VGA 4/3 Liquid Crystal Display

Display Type

Contrast

Black Level

Resolution

100 Ansi-Lumen

Projector 1000:1 full on/off 0,1000 min. Lumen

Offset

VGA 640 x 480 307.200 Pixel

SXGA 1280 x 1024 compressed

Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

The standard portable 103 HT LED LCD has 100 Ansi lumens, a contrast of 1000:1 and a VGA 640 x 480 resolution. The manufacturer specifies an LED service life of 50,000 hours, which is equivalent to 34.2 years at 4 hours of operation. The projector will be able to illuminate a picture

ω33 Lux (bei 200 cm Screen)

Application presentations.

Very narrow picture width and rooms with very little light.

Light Source Light Life

38W LED 50000 h.

Operating Costs

0,00 € LED

Focus

Zoom

Objective

Throw Ratio

Audio

D-sub 15 pin in S-Video in

Connections Cinch Video in

Ceiling Mounting

Power

300 x 109 x 250 mm (11,8"x4,3"x9,8") 8,18 L/dm3 Size WxHxD

Operating Noise 25dB

Weight 1,80 kg / 3,97 lbs. Keystone Vert.: +/-20°

Illumination

Frequenz

Foot-Lamberts 3 fL / max. 87 cm screen width

10 cd/m²

Features

Lux:33 Lux Room light max.:7 Lux Candela pro m²:10 cd/m² Foot-Lamberts:3 fL 4/3 screen width:200 cm Screen:1 Gain

Status Data - Discontinued (EOL) // Last update of the data: 2023-09-20

More Details



HCinema
https://www.projector-database.com/pro/chuangrong103ht-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.