



Brief Introduction

Beta 2.5

The standard portable EzPro 680 LCD has 500 Ansi lumens, a contrast of 250:1 and an XGA 1024 x 768 resolution. The projector will be able to illuminate a picture width of 195 cm well. However, if room light is available, the image width should ideally not exceed 130 cm. The model built in 1999 is no longer offered by CTX. It should also be noted that there are unfortunately no longer any replacement lamps available for the projector, neither originals nor replicas. 3 x 1,3" LCD TFT Panel

თ 162 Lux (bei 203 cm Screen) ი 250:1 full on/off 0 0.656 min. Lumen

Display Type

XGA 4/3 Liquid Crystal Display

Ansi-Lumen

500

Contrast Black Level

Offset

250:1 full on/off 2,0000 min. Lumen

XGA 1024 x 768

Resolution

786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes

Light Source

NTSC/PAL/SECAM

Standard-Portabel | External training and company presentations, as well as product

presentations. Application

Very narrow picture width and rooms with very little light.

250W Metalldampf Lamp Articel Nr.: SP.80701.001

Light Life 1000 h.

Operating Costs

Focus Powered

Zoom Powered 1,45

Objective F=2,0-2,3 f=38-55 mm

Throw Ratio 1,44-2,08:1

Audio 2 x 3W

Cinch Video in

Connections D-sub 15pin in und out

S-Video

Ceiling Mounting Power

340W

Size WxHxD 236 x 119 x 325 mm (9,3"x4,7"x12,8") 9,13 L/dm3

Operating Noise


Weight 5,40 kg / 11,9 lbs.

Illumination

Keystone

H-sync: 15-80 kHz Frequenz

V-sync: 50-85 Hz



Foot-Lamberts 15 fL / max. 195 cm screen width

51 cd/m²

Features

Status Data

1999 Discontinued (EOL) // Last update of the data: 2023-08-04

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.