

SPECIFICATIONS



COMPATIBILITY

Computer	Digital and Analogue PC, MAC, Workstation, 1400 and 1050 max. resolution, RGBHV, RGBS, RGsB
Mouse Compatibility	PS/2, MS Serial and USB, TCP/IP, RS-232, USB, Wired Remote
Video	HDCP, YPbPr, RGB, HDTV (1080i, 720p) S-Video, Composite Video PAL BGHI, M, N, SECAM, NTSC 3,58/4.43
Horizontal Scan Rate	15 - 100 Hz
Vertical Scan Rate	43 - 130 Hz
Bandwidth, Dot Clock	165 MHz analogue, 112 MHz digital

DISPLAY

Display	1.3" Polysilicon LCD x 3 with MLA (Micro Lens Array)
Brightness	3000 ANSI Lumens
Resolution	1024 x 768
Contrast Ratio	800:1
Lamp	270W SHP / life time up to 1500 hrs
Colour Reproduction	16.7 million colours

OPTICS

Lens	1.3 x manual zoom and focus, f = 47 - 61 mm, F/1.8 - 2.1
Image Size	0.5 - 7.8m / 27 - 300" diagonal
Throw Distance	1.1 - 11m / 4 - 36ft.
Throw Ratio	1.75 - 2.24 : 1 (distance : width)
Keystone Correction	optical 11.5 - 15.5 degrees, 9 : 1 up/down ratio

INPUT & OUTPUT

Computer 1,2	15-pin DSUB (VGA / VESA)
Computer 3	BNC x 5
Computer 4	DVI- D
Computer Audio	3.5 mm Stereo mini jack x 4
Mouse Control	USB / 6-pin PS/2
RGB/Component Video	BNC x 3
Video	RCA
S-Video	4-pin Mini DIN
Video Audio	RCA Stereo Audio
Monitor Out	15-pin DSUB (VGA / VESA) (Analogue Computer in only)
Audio Line Out	RCA Stereo Audio
RS-232 Control	9-pin DSUB
Wired Remote Control	2.5 mm Mini Jack
Speakers	5W Stereo Speakers, integrated 20W Subwoofer

NETWORK

Protocol	TCP/IP Based
Connection	Rj-45 10baseT Standard
Features	Asset Management, TCP/IP Control, Command and Control

METRICS

Size (W x L x H)	322 x 352 x 130 mm
Weight	6.0 KG

SUPPLIED MATERIAL & ACCESSORIES

Cables	Coaxial VGA cable 4m, A/V cable 4m, Power Cord 4m, USB Mouse cable 4m
Accessories	Dust Cover, Remote Control, Lens Cap, Start Adapter, User's Guide, MS Serial Mouse Adapter, PS/2 Mouse Adapter

GENERAL

Conformances	CE, UL, cUL, IRAM, NOM, FCC Class A
Operating Temp	10 - 35°C, 50 - 95°F (ambient operating)
Power Supply	100- 240V, 50/60 Hz
Power Consumption	<400W Normal Operation
Operating Noise	< 34 dB(A)

All specifications are subject to be changed without notice

DATAVIEW M320

Resolution	1024 x 768 (XGA)
Brightness	3000 ANSI lumens
Weight	6.0 kg



OTHER MULTIMEDIA PROJECTORS IN THE EXCLUSIVE DATAVIEW SERIES

DATAVIEW C181

Resolution	800 x 600 (SVGA)
Brightness	1000 ANSI lumens
Weight	2.6 kg



DATAVIEW C191

Resolution	1024 x 768 (XGA)
Brightness	1100 ANSI lumens
Weight	2.6 kg



DATAVIEW E101

Resolution	1024 x 768 (XGA)
Brightness	1100 ANSI lumens
Weight	3.7 kg



DATAVIEW E131

Resolution	1024 x 768 (XGA)
Brightness	1800 ANSI lumens
Weight	3.7 kg



DATAVIEW E221

Resolution	1024 x 768 (XGA)
Brightness	1500 ANSI lumens
Weight	3.4 kg



DATAVIEW E231

Resolution	1024 x 768 (XGA)
Brightness	2000 ANSI lumens
Weight	3.4 kg



Dataview M320

High Quality Projector
with excellent features
for professional
presenters



First Class Presentation Tools



DATAVIEW M320	
Resolution	1024 x 768 (XGA)
Brightness	3000 ANSI lumens
Weight	6.0 kg

Dataview