

E-Vision 4500 WUXGA 3D

4,000 ANSI Lumens | Contrast Ratio: 2,000:1 | Part No:114-782

E-Vision 4500 Series Digital Projectors

DIGITAL  **PROJECTION****Colour System:**

5-segment RYGBW Color Wheel

DMD Specification:

1920 x 1200 pixels native.

Fast transit pixels for smooth greyscale and improved contrast.

Display Type:

1 x 0.67" DarkChip™ DMD™

Aspect Ratio:

16x10

Fill Factor

87%

Key Features

Video & Graphics Processing

- HDMI 1.4 for Side by Side, Frame Packing & Top Bottom Formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display).
- Synchronisation of active glasses, DLP® Link™ glasses or polarising switcher.
- BrilliantColor™ for increased system brightness.
- Independent control of hue, saturation and gain for primary and secondary colors.
- High Bandwidth Digital & Analog Receiver with 10 Bit A-D.
- The projector automatically detects interlaced video and implements 3:2 or 2:2 extraction as appropriate, with pixel based, motion adaptive interpolation and auto cadence correction.
- 24p and 1080p native display.

Geometry Correction

- Vertical keystone correction.

Source Compatibility:

HDMI including Deep Color™ processing and 3D standards.

DVI with HDCP compliance.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DVI, DisplayPort or VGA.

Component Video (SD and HD) via YPrPb, RGBHV, RGB or RGBS.

S-Video (PAL, NTSC & SECAM)

Composite Video (PAL, NTSC & SECAM)

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.4	HDMI	1	LAN	RJ45	1
DVI-D	DVI	1	RS232	9-pin D Sub	1
DisplayPort	DisplayPort	1	Wired Remote	3.5mm Stereo Jack	1
VGA / Analog RGB In	15-pin D-Sub	2	12V Trigger	3.5mm Stereo Jack	1
VGA / Analog RGB Out	15-pin D-Sub	1	Service Port	USB Type B	1
Component Video	5 x BNC	1	1.5A USB charge	USB Type A	1
Component Video	3 x RCA	1	3D Sync Out	VESA 3-pin	1
S-Video	4-pin Mini DIN	1			
Composite Video	RCA	1			
Audio					
VGA Audio In	3.5mm Mini Jack	2			
VGA Audio Out	3.5mm Mini Jack	1			
Component Audio Out	2 x RCA Phono	1			
S-Video/Composite Audio In	2 x RCA Phono	1			
3D Formats Supported			HDTV Formats Supported		
Frame Sequential			1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz),1080i (50Hz,		
Top and Bottom			60Hz), 720p (50, 60Hz)		
Side By Side (half)					
Frame Packing					
Computer Compatibility			Bandwidth		
Up to 1920 x 1200			165 MHz on analog RGB		
			165 Megapixels per second on HDMI and DVI		
Remote Control			Automation Control		
IR remote control, wireless and wired.			RS232		
On-Board keypad			LAN		
Colour Temperature					
User selectable					
Lamp Type			Typical Lamp Life		
370W High Intensity Discharge			Full Power: 1500 hours		
			Eco Mode : 2000 hours		
Lenses					
Lens	Part No.	Focus Range	Lens Shift		
0.77: 1 fixed	114-785	0.4m - 3.1m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame		
1.54 - 1.93: 1 zoom	114-783	0.95m - 11.9m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame		
1.93 - 2.91: 1 zoom	114-784	1.2m - 29.8m	Vert: 0.55 (U) 0.15 (D) frame, Hor: 0.05 (L) 0.05 (R) frame		
Lens Mount					
Manual shift, zoom & focus.					
Mechanical Mounting			Orientation		
Front/Rear Table			Table Top or Inverted: Yes		
Front/Rear Ceiling			Pointing Up: Yes		
Adjustable Front/Rear Feet			Pointing Down: Yes		
			Roll (Portrait): +/-10° from horizontal		
Power Requirements			Power Consumption		
100-240VAC 50/60Hz single phase			450W		
Thermal Dissipation			Fan Noise		
1415 BTU/Hour			42 dBA, Eco 37 dBA		
Operating/Storage Temperature			Operating Humidity		
Operating: 5 to 35C (41 to 95F)			10 to 85% non-condensing		
Storage: -10 to 60C (14 to 140F)					
Weight (Chassis Only)			Dimensions		


8.6 kg
19 lb

L: 34.4 cm W: 43.1 cm H: 18.1 cm
L: 13.55 in W: 16.97 in H: 7.13 in

Safety & EMC Regulations

FCC Class B, cUL, UL, CE, C-tick, CCC, KC, CB, PCT

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*



Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[Important Information](#)

Specifications subject to change without notice. Digital Projection version: 1.1 - 29-Nov-12 ©2012 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, CHINA TOWER C, RM C1202, CAI FU JIA YUAN, NO. 19 XIAO YING STREET, CHAOYANG DISTRICT BEIJING, PR CHINA 100101
T: +86.10.58239771 | F: +86 10 58239770

