

Mercury 930 1080p 3D (Preliminary)

13,500 Lumens | Contrast Ratio: 2,000:1 | Part No:114-338

Mercury 930 Series Digital Projectors

DIGITAL  **PROJECTION**

Colour System:	DMD Specification:
3-chip DLP®	1920 x 1080 pixels native. Fast transit pixels for smooth greyscale and improved contrast.
Display Type:	Aspect Ratio:
3 x 0.95" DarkChip™ DMD™	16x9
	Fill Factor 87%

Key Features

Standard Inputs (1-8): Front End Video Capabilities

Video & Graphics Processing

- High bandwidth digital & analog receiver with 10 bit A-D.
- Automatic detection of interlaced video and implementation of 3:2 or 2:2 extraction as appropriate, with pixel based, motion adaptive interpolation and auto cadence correction.
- Displayed image frame locked to input with as low as 1 frame total latency.
- 24p and 1080p native display.
- Image enhancement for MPEG, Mosquito noise & color transients in composite sources.

Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Non-linear Warp adjustment by moving points on an interpolated grid.

Edge Blending

- Semi-automated multi projector tiling
- 12 bit processing and Black Level Uplift in blend region.
- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.

Super Image Clarity

- Geometry correction and Edge Blending implemented in single stage process, retaining maximum image resolution.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

ColorMax™

- Accurate matching of projectors in tiled or blended applications.
- User selection and storage of primary and secondary color targets.

High Bandwidth Inputs (9-11): Bypassing Front End for Minimal Latency

- Pixel mapped to the display.
- HDMI 1.4 for Side by Side, Frame Packing & Top Bottom formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources (example 144Hz display).
- FastFrame™ Smear Reduction.
- Dual Pipe processing: two sources in parallel for left and right eyes.
- Synchronisation of active glasses or polarising switcher.

Source Compatibility:

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

HDMI and DVI include Deep Color™ processing up to 36 bit.

DVI inputs are HDMI compatible.

Digital Audio Extraction via SPDIF for HDMI sources.

Graphics standards up to 1920 x 1200 at 60Hz via DVI or VGA.

Component Video (SD and HD) via YPrPb, RGB or RGBS.

S-Video (PAL, NTSC & SECAM)

Composite Video (PAL, NTSC & SECAM)

High Bandwidth, Pixel Mapped Path:

Dual Pipe accepts graphics standards up to 1920 x 1200 at 120Hz.

HDMI 1.4 including 3D Standards

Dual Pipe (2 x DVI)

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DVI-D / DVI-A	DVI-I	1	3D Sync Out	BNC	1
HDMI 1.3	HDMI	1	3D Sync In	BNC	1
3G-SDI	BNC	1	LAN	RJ45	1
HDBaseT	RJ45	1	RS232	9-pin D Sub	1
VGA / Analog RGB	15-pin D-Sub	1	Wired Remote In	3.5mm Stereo Jack	1
Component Video	4 x BNC	1	Wired Remote Out	3.5mm Stereo Jack	1
S-Video	4-pin Mini DIN	1	Service Port	USB Type B	1
Composite Video	RCA	1			
Composite Video	BNC	1			
High Bandwidth Ports					
Dual Pipe	DVI-D	1			
HDMI 1.4	HDMI	2			
Audio					
SPDIF Digital Output	RCA	1			

3D Formats Supported		HDTV Formats Supported	
Frame Packing Dual Pipe Frame Sequential Side By Side (half) Top and Bottom		1080p (23.98Hz, 24Hz, 25Hz, 29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz), 1080i (50Hz, 59.94Hz, 60Hz), 1080sf (23.98Hz, 24Hz), 720p (50Hz, 59.94Hz, 60Hz)	
Computer Compatibility		Bandwidth	
Up to 1920 x 1200		170 MHz on analog RGB 165 Megapixels per second on HDMI and DVI 330 Megapixels per second on Dual Pipe DVI	
Remote Control		Automation Control	
Addressable IR remote control, wireless and wired with loop-through. On-Board keypad		RS232 LAN	
Colour Temperature			
User selectable from 3200 to 9000K			
Lamp Type		Typical Lamp Life	
2 x 465W High Intensity Discharge		Full Power: 1500 hours (up to 3000 hours in lamp sequential mode) Eco Mode : 2000 hours (up to 4000 hours in lamp sequential mode)	
Lenses			
Lens	Part No.	Focus Range	Lens Shift
0.67:1 fixed HB	105-607	1.1m - 10m	Vert: 0.176 (U) 0.176 (D) frame, Hor: 0.063 (L) 0.063 (R) frame
1.12:1 fixed HB	105-608	3m - 15m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.12:1 (short) fixed HB	105-609	1.2m - 2m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.509 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.685 (U) 0.5 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
Lens Mount			
Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 5 user-definable preset positions.			
Mechanical Mounting		Orientation	
Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Optional RapidRig™ frame with integrated pitch, roll and yaw adjustments.		Table Top or Inverted: Yes Pointing Up: TBD Pointing Down: TBD Roll (Portrait): TBD	
Power Requirements		Power Consumption	
90 - 240VAC 50/60Hz single phase		TBD W	
Thermal Dissipation		Fan Noise	
TBD BTU/Hour		TBD	
Operating/Storage Temperature		Operating Humidity	
Operating: 0 to 40C (32 to 104F) Storage: -20 to 60C (-4 to 140F)		20% to 90% non-condensing	
Weight (Chassis Only)		Dimensions	
TBD kg TBD lb		L: 72 cm (approx) W: 51 cm (approx) H: 23 cm (approx) L: 28.3 in (approx) W: 20 in (approx) H: 9.1 in (approx)	
Safety & EMC Regulations			
CE, FCC Class A & B, UL, CCC, KC			
Downloads			

Specifications subject to change without notice. Digital Projection version: 1.3 - 31-May-13 ©2012 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, CHINA TOWER C, RM C1202, CAI FU JIA YUAN, NO. 19 XIAO YING STREET, CHAOYANG DISTRICT BEIJING,
PR CHINA 100101
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238