Digitel DGT X31U



Brief Introduction
Beta 2.5

resolution and a contrast of 500:1. A built-in horizontal and vertical keystone correction provides freedom when positioning the projector. An image width of up to 485 cm is possible. However, the image should be smaller in room light. We recommend max. 323 cm. This model is no longer offered by Digitel.

დ1033 Lux (bei 200 cm Screen)

Display Type

XGA 4/3 Liquid Crystal Display

3 x 0,99" LCD TFT Panel

Ansi-Lumen
Contrast
Black Level
Offset

Og 500:1 full on/off
6,2000 min. Lumen

500:1 full on/off 500:1 full on/off 500:1 full on/off 2,000 min. Lumen 2,078 min. Lumen 3 XGA 1024 x 768

Resolution 786.432 Pixel UXGA 1600 x 120

UXGA 1600 x 1200 compressed

Video Modes PAL, PAL-M, PAL-N, PAL-60, SECAM, NTSC, EDTV HDTV 720p, 1080i,

Standard-Portabel | External training and company presentations, as well as product

Application presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source UHP Lamp Light Life -

..9...

Operating Costs

Zoom

Focus Manual

Objective -

Throw Ratio -

Audio -

DVI-I

Manual

D-sub 15pin in Cinch Video in S-Video in Mini Jack

Mini Jack USB RS232C

Ceiling Mounting

Connections

Power 350 / 260W in Eco Mode

Size WxHxD 364 x 110 x 285 mm (14,3"x4,3"x11,2") 11,41 L/dm³

Operating Noise 37 / 32 dB in Eco Mode

Lux:1033 Lux
Room light max.:207 Lux
Candela pro m²:329 cd/m²
Foot-Lamberts:96 fL

4/3 screen width:200 cm
Screen:1 Gain

Weight 4,60 kg / 10,14 lbs.

Keystone Vert.: +/-15°
Hori.: +/-10°

Illumination 80%

H-sync: 15-100 kHz V-sync: 43-120 Hz Range max.: 230 MHz

Foot-Lamberts 96 fL / max. 485 cm screen width

 329 cd/m^2

- Discontinued (EOL) // Last update of the data: 2023-08-04

Data

Frequenz

Status









Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.