## **Digitel DGT X42U**



Brief Introduction
Beta 2.5

projector can also handle slightly brighter rooms with a smaller image width (we recommend max. 376 cm). This model is no longer offered by Digitel.

3 x 0,99" LCD TFT Panel

XGA 4/3 Liquid Crystal Display

Display Type
Ansi-Lumen

Contrast

Offset

Black Level

P 4200

5. 500:1 full on/off 8,4000 min. Lumen

-

XGA 1024 x 768
Resolution 786.432 Pixel

UXGA 1600 x 1200 compressed

Video Modes PAL, PAL-M, PAL-N, PAL-60, SECAM, NTSC, EDTV HDTV 720p, 1080i,

Standard-Portabel | External training and company presentations, as well as product

Thanks to the brightness of 4200 Ansi lumens, a picture width of 564 cm is possible. The

φ1400 Lux (bei 200 cm Screen)

2,817 min. Lumen

Application presentations.

Wide screen width or rooms with plenty of light (over 200 lumens).

Light Source Light Life UHP Lamp

Operating Costs

Focus Manual

Zoom Manual

Objective -

Throw Ratio -

Audio -

DVI-I

D-sub 15pin in Cinch Video in S-Video in Mini Jack

Mini Jack USB RS232C

Ceiling Mounting

Connections

Power 350 / 260W in Eco Mode

Size WxHxD 364 x 110 x 285 mm (14,3"x4,3"x11,2") 11,41 L/dm<sup>3</sup>

Operating Noise 37 / 32 dB in Eco Mode

Lux:1400 Lux

Room light max.:280 Lux
Candela pro m²:445 cd/m²
Foot-Lamberts:130 fL

4/3 screen width:200 cm
Screen:1 Gain

Weight 4,60 kg / 10,14 lbs.

Keystone Vert.: +/-15°
Hori.: +/-10°

Illumination 80%

H-sync: 15-100 kHz V-sync: 43-120 Hz Range max.: 230 MHz

Foot-Lamberts 130 fL / max. 564 cm screen width

445 cd/m<sup>2</sup>

- Discontinued (EOL) // Last update of the data: 2023-08-04

Data

Frequenz

Status









Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.