DOW UC300



Brief Introduction

Beta 2.5

Display Type

A brief introduction to the UC300: The DOW standard portable LCD projector offers 1500 Ansi lumens, a contrast of 200:1 and a WVGA 800 x 480 resolution. The projector can illuminate an image width of up to 393 cm with its 1500 Ansi lumens. In room light, however, the image width should ideally be less than 262 cm. This model is no longer offered by DOW.

1 x LCD TFT Panel

WVGA 16/9 Liquid Crystal Display

Ansi-Lumen 1500 200:1 Contrast

Black Level 7,5000 min. Lumen

Offset

WVGA 800 x 480 Resolution 384.000 Pixel

XGA 1024 x 768 compressed

Video Modes Pal, SECAM, NTSC,

Standard-Portabel | External training and company presentations, as well as product

Application presentations.

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

270W Lamp 2000 h.

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

D-sub 15 pin in S-Video in Cinch Video in

Ceiling Mounting

Connections

Power

345 x 105 x 255 mm (13,6"x4,1"x10") 9,24 L/dm3 Size WxHxD

Operating Noise

5,80 kg / 12,79 lbs. Weight

Keystone Illumination

Frequenz


Foot-Lamberts 62 fL / max. 393 cm screen width

212 cd/m²

Features

Status - Discontinued (EOL) // Last update of the data: 2023-08-04

Data



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.