Dukane ImagePro 8048





Brief Introduction

Beta 2.5

The Dukane ImagePro 8048 stationary LCD projector has 1300 Ansi lumens, a contrast of 400:1 and an SVGA 800 x 600 resolution. The projector can illuminate a picture width of up to 314 cm thanks to the 1300 Ansi lumens. In room light, however, the image width should ideally be less than 209 cm. The projector is no longer sold by the manufacturer.

Display Type

3 x 0,7" LCD TFT Panel SVGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast Black Level

Light Source

Focus

1300 400:1 full on/off 3.2500 min. Lumen Lux:421 Lux

4/3 screen width: 203 cm

Screen:1 Gain

Room light max.:84 Lux Candela pro m²:134 cd/m²

Foot-Lamberts:39 fL

ัด 400:1 full on/off ปี 1.061 min. Lumen

Offset

SVGA 800 x 600 480.000 Pixel

Resolution Video Modes

NTSC, NTSC 4.43, PAL, MPAL, NPAL, PAL60, Stationary | Permanent installation in the training room and meeting room as well as the

Application conference room.

Small screen width, rooms with very little ambient light below 100 lumens.

270W SHP Lamp Articel Nr.: 456-216

Light Life 2000 h.

Operating Costs

Manual

Zoom Manual 1,25

Objective

Throw Ratio

1 x 2,5W Audio

Connections M1-DA DVI Analogmit USB, Composite video, S-video

Ceiling Mounting Power Size WxHxD Operating Noise

Keystone

Vert. +12°-0°

Foot-Lamberts 39 fL / max. 314 cm screen width

■ Remote control with laser pointer

Overscan adjustable

Data



https://www.projector-database.com/pro/dukaneimagepro8048-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.

C X ≥

Weight

Illumination

Frequenz

Features

Status

More Details

134 cd/m² ■ Eco Mode

- Discontinued (EOL) // Last update of the data: 2023-08-04