



ImagePro 8077 Portable LCD Projector

- 2000 Lumens Brightness
- SVGA Resolution
- 400:1 Contrast Ratio
- Auto Vertical Keystone Correction
- Auto Ceiling Detection
- Auto Brightness Control
- Monitor Loopthrough
- RS232 for Control and USB for Remote Mouse Capability



8077 DUKANE

ImagePro 8077

Super Bright LCD projector

The Dukane ImagePro 8077 is an outstanding value projector for your classroom or conference room.

Auto keystone correction, ceiling detection, and brightness control make this projector fast and easy to set up.



Key features:

- SVGA (800 x 600) Resolution
- 2,000 ANSI Lumens of Brightness
- 400:1 Contrast Ratio
- Easy Carry, 6 lbs.
- Flexibility with 2 Computer and 2 Video inputs
- Auto Vertical Keystone Correction
- Auto Ceiling Detection
- Auto Brightness Control
- Monitor Loopthrough
- RS232 for Control and USB for Remote Mouse Capability
- Two Year Warranty and One Year Peace of Mind Service

8077 Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	3.6	4.3
40	32	4.8	5.7
50	40	6.0	7.1
60	48	7.2	8.6
80	64	9.5	11.4
100	80	11.9	14.3
200	160	23.9	28.5
300	240	35.8	42.8

Throw Ratio (distance to width) 1.79 2.14

DUKANE

Dukane Corporation
Audio Visual Products Division
2900 Dukane Drive
St. Charles, Illinois 60174
800-676-2485
630-584-5156
avsales@dukcorp.com
www.dukcorp.com/av

toll-free
fax
e-mail



ImagePro is a registered trademark of Dukane Corporation
#11700-E-06

Specifications

Image Element	0.7" polysilicon TFT x3, MLA
Brightness	2000 ANSI lumens 1600 (whisper mode)
Resolution	800 x 600 (H x V), SVGA
Contrast	400:1
Scanning Frequency	fh 15-69 kHz, fv 43-85 Hz
Lens	Manual zoom and focus (F=1.8 to 2.1), 1.2X
Lens Throw Ratio	1.79 -2.14 :1 throw distance to image width
Keystone Correction	Digital, vertical +/-30 deg, automatic
Aspect Ratio	4:3, 16:9 selectable
Computer Compatibility	VGA, SVGA, XGA SXGA compressed, MAC
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV 1080i, 720p, 480i/p
Image Control	Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	180W
Lamp Life	2000 hours (3000 in whisper mode)
Audio	1W x 1
Throw Distance	60" to 445"
Screen Size, diagonal	40" to 300"
Inputs, Video	(1) Composite video, RCA x 1 (1) S-video, Min DIN 4-pin, (2) RGB Signal: D-sub, 15 pin
Inputs, Computer	Audio, Stereo mini-jack x 1
Outputs Monitor	15 pin, D-sub
Outputs Audio	Audio, Stereo mini jack x 1
Outputs, Control	9 pin D-sub Connector, RS232C USB connector x 1
Security	Kensington lock slot
Fan Level	37dB, (33dB in whisper mode)
Operating Temperature	41 to 95 deg. F (5-35 deg C)
Power	AC 100-120V, AC220-240V, 50/60 Hz 250W (normal), 232W (whisper), >5W (standby)
Size (WxHxD)	12" x 4" x 10.5"
Weight	6 lbs.
Carton Size	18" x 9" x 14"
Shipping Weight	18 lbs.
Accessories Included	Remote control, battery, power cord, S-Video cable, VGA cable, RCA video cable, Mini-jack audio cable, Filter, Quick Start Guide, User Manual, CD ROM, and Soft Carry Case
Safety	UL, cUL, FCC, CE, CB, CCC
Optional Accessories	Lamp 456-8077 Wireless Extender, LV3500W Ceiling mount, universal; RPA-U

Two (2) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

2YR