

Dukane ImagePro 8412



DUKANE IMAGEPRO 8412



Brief Introduction

Beta 2.5

The short-throw ImagePro 8412 3D BrilliantColor DLP projector from Dukane has 3100 Ansi lumens, a contrast of 3000:1 and a WXGA 1280 x 800 resolution. Thanks to the short-throw projection ratio of just 0.52:1, the projector does not stand out in the room. For a 2m wide image, the projector only needs to be 104 cm away from the screen. As the ImagePro 8412 is equipped with a microphone jack plug and 10W speakers, no additional audio system is required for presentations or training courses. Even 1080P video signals are no problem for the projector. The operating noise of just 29 decibels makes the projection quiet. The model built in 2011 is no longer offered by Dukane.



1 x 0,65" DC3 DLP Chip

WXGA 16/10 Ti Digital Light Processing Chip

Display Type

Ansi-Lumen

Projector 3100

Screen 1240 Lux (bei 200 cm Screen)

Contrast

3000:1 full on/off

Screen 3000:1 full on/off

Black Level

1,0333 min. Lumen

Screen 0,414 min. Lumen

Offset

Resolution

WXGA 1280 x 800

1.024.000 Pixel

UXGA 1600 x 1200 compressed

Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, 1080p EDTV 480p, 576p

Disc Recognition

DVD | HD Blu-ray (komprimiert) | 3D Blu-ray | 4K UHD Blu-ray

3D Compatibility

Frame Sequential (3D Ready)

120Hz Frame Sequential 3D for Resolutions Up to 720p,
60Hz Field Sequential 3D for Resolutions Up to 480i

Application

Short Distance | Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source

-

Articel Nr.: 23.8BW15G004

Light Life

3000 h. 4000 h. in Eco Mode

Operating Costs

-

Focus

Manual

Zoom

No Zoom

Objective

F=2,8 f=7,35mm

Throw Ratio

0,52:1

Audio

10W

Connections

HDMI in
2 x D-sub 15 pin in 1 x out
S-Video in
Cinch Video in
Cinch Stereo in
Mini Jack in
RS232C Din 8 pin in
RJ45 in
Mikrofon in

Ceiling Mounting

Yes

Power

295W

Size WxHxD

306 x 113 x 243 mm (12"x4,4"x9,6") 8,4 L/dm³

Operating Noise

29dB



Key: 165 cm

Weight	3,10 kg / 6,83 lbs.
Keystone	Vert.: +/-40°
Illumination	85%
Frequenz	H-sync: 15-91 kHz V-sync: 25-85 Hz
Foot-Lamberts	115 fL / max. 566 cm screen width 394 cd/m²
Features	Full HD 1080P compatible Eco Mode Kensington Slot Password protection BrilliantColor™ Remote control with mouse control Lan network compatible. Short-throw projector Crestron®-Software compatible. Digital Zoom 2x
Optional	Remote control original BR-5023L / BR-3057L / BR-5029L / BR-5030L / BR-5033L
Status	Order here: https://www.hcinema.de/lampen/shop-en.php?id=fro20090
Data	2011 Discontinued (EOL) // Last update of the data: 2023-08-04



More Details



HCinema

<https://www.projector-database.com/pro/dukaneimagepro8412-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.