









Brief Introduction

Display Type

Black Level

Offset

Beta 2.5

The ImagePro 8784 LCD has 2000 Ansi lumens, a contrast of 500:1 and an XGA 1024 x 768 resolution. The projector can illuminate an image width of up to 389 cm thanks to its 2000 Ansi lumens. In room light, however, the image width should ideally be less than 259 cm. The model was built by Dukane in 2008 and is no longer current.

3 x 0,63" LCD TFT Panel XGA 4/3 Liquid Crystal Display

φ667 Lux (bei 200 cm Screen) Ansi-Lumen 2000 / 1600 im Eco Mode Contrast

Ω 500:1 full on/off Ω 1,342 min. Lumen 500:1 full on/off 4,0000 min. Lumen

XGA 1024 x 768 Resolution 786.432 Pixel

UXGA 1600 x 1200 compressed

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Application

Medium screen width or rooms with little light, max. 100 lumens.

160W UHB Lamp Light Source Articel Nr.: 456-8770

Light Life 2000 h. 3000 h. in Eco Mode

Operating Costs

Focus Manual

Zoom Manual 1.2

Objective F=1,8-1,9 f=16,4-19,7 mm

Throw Ratio 1,28-1,54:1

Audio 1 x 1W

> D-sub 15 pin in S-Video in Cinch Video in Mini Jack in USB in **RJ45**

SD Slot Yes

Ceiling Mounting Power

Connections

250W

274 x 65 x 205 mm (10,8"x2,6"x8,1") 3,65 L/dm3 Size WxHxD

Operating Noise 35 / 29 dB in Eco Mode

Weight 1,90 kg / 4,19 lbs.

Keystone Vert.: +/-30° automatisch


Illumination


H-sync: 15-91 kHz Frequenz

V-sync: 50-120 Hz

Foot-Lamberts 62 fL / max. 389 cm screen width

212 cd/m²





■ Freeze

■ Blackboard Modus

■ User logo

■ Eco Mode

■ Automatic and manual vertical keystone correction

■ Kensington Slot

■ Gamma correction

■ Password protection

■ Remote control with mouse control

■ Wi-Fi network compatible.

■ Lan network compatible.

■ De-interlacer with 3:2 pull down...

2008 Discontinued (EOL) // Last update of the data: 2023-08-04

Data

Status

Features



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.