## **Dukane ImagePro 8941A**









**Brief Introduction** 

Beta 2.5

A brief introduction to the ImagePro 8941A: The Dukane standard portable LCD projector offers 4500 Ansi lumens, a contrast of 500:1 and an XGA 1024 x 768 resolution. An image width of up to 584 cm is possible, if the image width is smaller (we recommend max. 389 cm), rooms with residual light are also no problem. This model is no longer offered by Dukane. 3 x 1,3 LCD TFT Panel

2.93 min. Lumen

დ 1456 Lux (bei 203 cm Screen)

Display Type

Ansi-Lumen

**Black Level** 

Resolution

Light Source

Contrast

Offset

XGA 4/3 Liquid Crystal Display

4500 / 3600 im Eco Mode

500:1 full on/off 9,0000 min. Lumen

XGA 1024 x 768

786.432 Pixel

SXGA 1280 x 1024 compressed

NTSC, PAL, MPAL, NPAL, PAL60, SECAM, Component, 480i, 575k, 480p, 1080i, 720p, HDTV Video Modes

Standard-Portabel | External training and company presentations, as well as product

Application presentations.

Wide screen width or rooms with plenty of light (over 200 lumens).

275W UHB Lamp Articel Nr.: 456-225

2000 h. Light Life

**Operating Costs** 

Powered **Focus** 

Zoom Powered 1,3

Objective F=1,7-2,3

Throw Ratio

Audio 2 x 1,2W

Screen:1 Gain

Inputs, Video (1) Component, RCA x 3, (1) Min DIN 4-pin, S-Video, (1) RCA, Composite Video,

(1) Audio, Stereo mini jack, (1) DVI, Digital Visual Interface

Inputs, Computer (2) Signal; D-sub 15pin, (2) Audio, Stereo mini jack Connections

Outputs, Control 15 pin, D-sub, RS232C

Outputs, Computer (1) Signal, D-sub 15pin, (1) Audio, Stereo Mini jack Yes

Ceiling Mounting Power

440W

Size WxHxD


Operating Noise 40 / 36 dB in Eco Mode

Weight Keystone Illumination

Frequenz

135 fL / max. 584 cm screen width Foot-Lamberts

463 cd/m<sup>2</sup>



Freeze

■ Blank (Black screen button)

**■** Eco Mode

■ Kensington Slot

Gamma correction

■ Remote control with laser pointer und mouse control

- Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

**Features** 



More Details

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.