

LC-XIP2600



- Anti-Dust model "Double Layer Anti-Dust Filter"
Suitable for tough environments : Sand, Dust, Chalk dust, Fungus, Pollen and Coarse dust.
- Interactive function permit real-time annotation of projected image.
- Pen & Pointer function as both writing instruments & computer mouse.
- XGA Short Throw Projector/ Brightness 2600 lumens (Powerful mode)
- 6 Auto functions: "Auto-" Search, Sync, Ceiling, Keystone, Filter Alert and Lamp Usage Alert
- Power-OFF and GO "10 seconds"
- Closed Captioning function(USA market only)
- Customized Logo
- Free installation: Vertical 360 degrees
- More Security Built-in security bar.
- Easy maintenance: Side change filter & lamp
- Built-in 8W audio speaker
- LAN (RJ-45)



SPECIFICATIONS

Color system	PAL / SECAM / NTSC/ NTSC 4.43 / PAL-M / PAL-N / PAL60
Computer compatibility	UXGA* / SXGA+ * / SXGA* / WXGA* / XGA / SVGA / VGA
Screen size (diagonal)	40" ~ 300"
Throw distance	0.77 m ~ 7.37 m *Approx. 100" at 2.0m (50"~150": interactive function available)
Throw ratio	0.96 ~ 1.18 : 1
Brightness	2600 / 1800 lumens (Powerful / Normal mode) *Default setting Normal mode.
Contrast ratio	500:1
Panel	0.63" Polysilicon TFT active matrix LCD *Organic type.
Number of pixels	786,432 (1024 x 768) x 3
Projection lens	f = 18.53 ~ 22.18 mm, F 1.65 ~ 1.93 Zoom(x 1.2)
Projection lamp	230 W / 185 W (Powerful / Normal mode) NSHA
Lamp Life	3000 H / 2000H (Normal / Powerful mode)
Digital Keystone	U/L : +/- 30 degrees
Image Elevation Adjustment	Up to 8.5 degrees
Power consumption	315 W / 250 W , Standby 5 W / 3 W (Powerful / Normal mode)
Scanning frequency	H sync : 31 ~ 92 kHz, V sync : 48 ~ 120 Hz, Dot Clock : 162 MHz
Operating voltage	AC 100 ~ 240 V, 50/60 Hz
Operating temperature	5 - 35 celsius degrees
Fan noise	34 / 40 dBA (Normal / Eco mode)
Computer Input	DVI-I (HDCP) x 1(Digital RGB), Dsub15 x 1(Analog RGB)
Computer Output	Dsub15 (Analog RGB) x 1
Video Input	Mini DIN 4-pin (S-Video) x 1, RCA x 1 (Composite), RCA x 3 (Component)
Audio Input	Mini jack x 2, RCA (L,R) x 1
Audio Output	Mini jack x 1
Control	Dsub9 (RS-232C) x 1
Others	USB type B x 1 LAN (RJ-45)
Speaker	8W x1
Dimensions (WxHxD)	316.2 x 117.8 x 325.0 mm(12.44 x 4.63 x 12.79 inch) *including projection
Weight	3.87 kg(8.53 lb)
Packaged dimensions (WxHxD)	242.0 x 429.0 x 487.0 mm(9.52 x 16.88 x 19.17 inch) *target
Packaged weight	6.2 kg(13.66lb) *target
REGULATIONS	UL(c/us), FCC, CE, CB , CCC
Standard Accessories	Owner's Manual (CD-ROM) x 1, Quick guide x 1, Remote control(with AAA batteries x 2) x 1, Power cord (1.8m), Computer cable (1.5m) x 1, USB cable (1.5m) x 1, LAN & Application soft(CD-ROM), Pen(with AAA batteries x2), Pointer(with AA batteries x2), Soft case(for Pen & Pointer)

*Compression

*Specifications subject to change without notice. ver.Rev.1c 090525