Eiki LC 4200





Application

Operating Costs

Focus

Zoom

Brief Introduction Beta 2.5

lamps for this model, neither originals nor replicas. 3 x 1,3" LCD TFT Panel Display Type

VGA 4/3 Liquid Crystal Display 200 Ansi-Lumen ω65 Lux (bei 203 cm Screen)

ชัก 100:1 6 0.67 min. Lumen 100:1 Contrast Black Level 2,0000 min. Lumen

Offset

VGA 640x480 Resolution 307.200 Pixel Video Modes PAL, NTSC

Stationary | Permanent installation in the training room and meeting room as well as the

A brief introduction to the Eiki LC 4200. The LCD projector has a VGA 640x480 resolution and a

However, if room light is available, the picture width should ideally not exceed 82 cm. The model

built in 1997 is no longer offered by Eiki. Unfortunately, we can no longer offer replacement

contrast of 100:1. The projector will be able to illuminate a picture width of 123 cm well.

conference room.

Very narrow picture width and rooms with very little light.

195W Metalldampf Lamp Light Source Articel Nr.: 610-257-6269

Manual

Manual 1,3

2000 h. Light Life

Objective F=2,8-3,2 f=53-69 mm

Throw Ratio 2,01-2,61:1

3W Mono Audio

> Cinch Video in S-Video in Cinch Stereo in

Ceiling Mounting

Power

Size WxHxD 430 x 158 x 385 mm (16,9"x6,2"x15,2") 26,16 L/dm³

Operating Noise

Weight Keystone

Connections

9,90 kg / 21,83 lbs.


Illumination

H-sync: 15-37,9 kHz Frequenz V-sync: 50-70 Hz

Foot-Lamberts 6 fL / max. 123 cm screen width

21 cd/m²

Features



Status Data 1997 Discontinued (EOL) // Last update of the data: 2023-08-04

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.