eLux EX2025W







Brief Introduction

Beta 2.5

of 500:1. 2600 Ansi lumens ensure that a picture width of 444 cm is also possible. However, if room light is available, the picture should be max. 296 cm wide. The model was built by eLux in 2008 and is no longer current. 3 x 0,63" LCD TFT Panel mit MLA

The eLux model EX2025W is an LCD projector with XGA 1024 x 768 resolution and a contrast

Display Type

XGA 4/3 Liquid Crystal Display with Micro Lense Array

Ansi-Lumen Contrast Black Level

P 2600 ୍ରିଟ 500:1 full on/off 5,2000 min. Lumen 500:1 full on/off

ω867 Lux (bei 200 cm Screen) Ω 500:1 full on/off 1,744 min. Lumen

Resolution

Offset

XGA 1024 x 768

786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Application

presentations. Medium screen width or rooms with little light, max. 100 lumens.

200W NSH Lamp

Light Source Light Life

2000 h. 3000 h. in Eco Mode

Operating Costs

Manual

Zoom

Focus

Manual 1,2

Objective

F=1,44-1,88 f=18,6-22,3 mm

Throw Ratio

Connections

1,45-1,74:1

Audio

2W Mono

D-sub 15 in und out S-Video in

Cinch Video in

RS232C

USB

Mini Jack in und out

Ceiling Mounting

Yes

Power

250W

Size WxHxD

310 x 96 x 270 mm (12,2"x3,8"x10,6") 8,04 L/dm³

Operating Noise 30 dB in Eco Mode

Weight Keystone

Frequenz

3,30 kg / 7,28 lbs.

Vert.: +/-30° automatisch


Illumination


H-sync: 15-69 kHz V-sync: 43-85 Hz

Range max.: 110 MHz

Foot-Lamberts 81 fL / max. 444 cm screen width

278 cd/m²





Features

Freeze ■ Eco Mode

■ Automatic and manual vertical keystone correction

Remote control with laser pointer

Status Data

2008 Discontinued (EOL) // Last update of the data: 2023-08-04

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.