eLux LX300









Brief Introduction Beta 2.5

Display Type

Resolution

Application

The eLux LX300 LCD projector has 3000 Ansi lumens, a contrast of 500:1 and an XGA 1024 x 768 resolution. As the projector has horizontal and vertical keystone correction, the projector can be set up with plenty of free space in the room. The projector will be able to illuminate a picture width of 477 cm well. However, if room light is available, the picture width should ideally not exceed 318 cm. This model is no longer available from eLux.

ω971 Lux (bei 203 cm Screen)

ទី 500:1 full on/off ១ 1.954 min. Lumen

3 x 0,99" LCD TFT Panel mit MLA

XGA 4/3 Liquid Crystal Display with Micro Lense Array

Ansi-Lumen 3000 500:1 full on/off Contrast Black Level 6,0000 min. Lumen Offset

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

PAL, PAL-M, PAL-N, PAL-60, SECAM, NTSC, EDTV HDTV 720p, 1080i, 1080i, Video Modes

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

250W Lamp

Light Source Articel Nr.: LMP17099

2000 h. 3000 h. in Eco Mode Light Life

Operating Costs

Focus manuell

Zoom Manual 1,3

Objective

Throw Ratio 1.84-1.41:1

Audio 1 x 2W Mono

DVI-I

D-sub 15pin in und out

YUV in

Cinch Video in Cinch Stereo in S-Video in Mini Jack

USB RS232C



Ceiling Mounting Power

Connections

350W

Size WxHxD 363 x 109 x 284 mm (14,3"x4,3"x11,2") 11,24 L/dm3

Operating Noise 35dB

374 - 286 cm Lux:971 Lux Room light max.: 194 Lux Candela pro m²:308 cd/m² Foot-Lamberts:90 fL 4/3 screen width: 203 cm Screen:1 Gain

Key: 100 cm

Weight 5,90 kg / 13,01 lbs.

Keystone Vert.: +/-15°

Hori.: +/-10°

Illumination -

Frequenz H-sync: 15-100 kHz V-sync: 43-120 Hz

Foot-Lamberts 90 fL / max. 477 cm screen width

308 cd/m²

Freeze

■ Picture-in-Picture

Please note

Status - Discontinued (EOL) // Last update of the data: 2023-08-04

Data



More Details



Key: 66 cm

Without offset ...

Key: 100 cm

Key: 66 cm

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.