

NEW

VS350 XGA 3LCD Projector

Contact Us 800.463.7766

Mon-Fri 6am-8pm, Sat 7am-4pm PT



Portable projector with HDMI® for presentations with greater detail.

Travel friendly and easy to use, the VS350 portable projector delivers 3,300 lumens of color/white brightness¹ for vivid, colorful images — even in well-lit rooms. Featuring XGA resolution (1024 x 768) — 1.5x more than SVGA — the VS350 is ideal for more detailed, text-heavy presentations. Its simple image adjustment and setup tools get you up and running quickly. Plus, Epson® 3LCD projectors deliver remarkable color accuracy, with up to 3x Higher Color Brightness² and up to 3x Wider Color Gamut³ over competitive DLP projectors. The VS350 also supports HDMI, the standard in digital connectivity, for use with the latest laptops and media players.

Projection System: 3LCD, 3-chip technology**Native Resolution:** 1024 x 768 (XGA)

Color Brightness: 3300 lumens¹

White Brightness: 3300 lumens¹

Throw Distance Calculator

Model: V11H839220

OUR PRICE :

\$429.99



[Write a review](#)

Overview

Specifications

Specifications Projector:

Projection System:

Epson 3LCD, 3-chip technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

786,432 dots (1024 x 768) x 3

Color Brightness - Color Light Output:

3300 lumens¹

White Brightness - White Light Output:

3300 lumens¹

Aspect Ratio:

4:3

Native Resolution:

1024 x 768 (XGA)

Resize:

800 x 600 (SVGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+)

Lamp Type:

210 W UHE

Lamp Life:

- ECO Mode: Up to 10000 hours⁶
- Normal Mode: Up to 6000 hours⁶

Throw Ratio Range:

1.48 (Zoom:Wide), 1.77 (Zoom:Tele)

Size - projected distance:

30" – 300" (0.9 – 9.0m)

Keystone Correction:

- Automatic: Vertical: ± 30 degrees
- Horizontal: Easy-slide, Image correction

USB Plug 'n Play:

Projects audio and video, PC and Mac® compatible

Contrast Ratio:

Up to 15,000:1

Color Reproduction:

Up to 1.07 billion colors

General:

Temperature:

41° to 95° F (5° to 35° C)

Weight:

5.5 lb

Security:

Password Protect function

Projection Lens:

Type:

Optical zoom (Manual)/Focus (Manual)

F-number:

1.49 – 1.72

Focal Length:

16.9 mm – 20.28 mm

Zoom Ratio:

Optical zoom 1.0 – 1.2

Projector Details:

Display Performance:

- NTSC: 480 lines
- PAL: 560 lines
(depends on observation of the multi-burst pattern)

Input Signal:

NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM

Interfaces:

- HDMI x 1

- Computer / Component video: D-sub 15 pin x 1
- Composite video: RCA (Yellow) x 1
- Audio in: RCA (White / Red) x 1
- USB connector: Type A x 1 (PC-free and other)
- USB connector: Type B x 1 (USB Plug 'n Play)

Speaker:

1 W (Mono)

Fan Noise:

- ECO mode: 28 dB
- Normal mode: 37 dB

Projector Dimensions:

Including feet:

11.9" x 9.3" x 3.2" (W x D x H)

Excluding feet:

11.9" x 9.2" x 3.0" (W x D x H)

Remote Control:

Features:

Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions

Operating Distance:

19.7' (5.8 m)

Operating Angle:

- Right / Left: ± 30 degrees
- Upper / Lower: ± 15 degrees

Power:

Power Supply Voltage:

100 – 240 V $\pm 10\%$, 50/60 Hz

Power Consumption:

- ECO mode: 211 W
- Normal mode: 295 W