Everest ED U61





Brief Introduction Beta 2.5

The Everest ED U61 standard portable LCD projector has 2600 Ansi lumens, a contrast of 500:1 and an XGA 1024 x 768 resolution. An image width of up to 444 cm is possible as the projector has 2600 Ansi lumens. However, if room light is available, the picture should be max. 296 cm wide. The model was built by Everest in 2006 and is no longer current.

3 x 0,7" LCD TFT Panel XGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast

Display Type

2600 500:1 full on/off 5,2000 min. Lumen ω867 Lux (bei 200 cm Screen)

500:1 full on/off 1,744 min. Lumen

Black Level Offset

Video Modes

Application

Resolution

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

Light Source Light Life

Focus

200W NSH Lamp 2000 h.

Operating Costs

Manual

Zoom Manual 1,2

Objective F=1,8-2,1 f=26,5-31,5 mm

Throw Ratio 1,86-2,22:1

Audio 2 x 1W

D-sub 15 in und out


S-Video in Cinch Video in **RS232C USB**

Connections Mini Jack in und out



Ceiling Mounting Power

Yes 250W



Size WxHxD 310 x Operating Noise 33 / 3

310 x 96 x 270 mm (12,2"x3,8"x10,6") 8,04 L/dm³ 33 / 30 dB in Eco Mode

Weight 2,70 kg / 5,95 lbs. Keystone Vert.: \pm Vert.: \pm

Illumination -

Frequenz H-sync: 15-100 kHz V-sync: 43-120 Hz

Foot-Lamberts 81 fL / max. 444 cm screen width

278 cd/m² ■ Eco Mode

Features Remote control with laser pointer

Status 2006 Discontinued (EOL) // Last update of the data: 2023-08-04

Data







More Details





Key: 215 cm

Key: 215 cm

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.