Fujitsu LPF 7200









Brief Introduction Beta 2.5

The Fujitsu model LPF 7200 is an LCD projector with XGA 1024 x 768 resolution and a contrast of 300:1. An image width of up to 461 cm is possible, as the projector has 2800 Ansi lumens. However, if room light is available, the image should be max. 307 cm wide. This model is no longer offered by Fujitsu. It should also be noted that, unfortunately, there are no more replacement lamps for the projector, neither originals nor replicas.

Display Type

1,3 psi TFT Panel

XGA 4/3 Liquid Crystal Display

Ansi-Lumen

2800 ω906 Lux (bei 203 cm Screen)

Contrast Black Level

300:1 full on/off 9,3333 min. Lumen ਰੂੰ 300:1 run ਹਨ. ਤੋਂ 3.051 min. Lumen 300:1 full on/off

Offset

XGA 1024 x 768

Resolution

786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes

PAL, SECAM, NTSC (auch 4,43), MPAL, NPAL

Application

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Medium screen width or rooms with little light, max. 100 lumens.

Light Source

250W NSH Lamp

Articel Nr.: LPF-P697

Light Life

1500 h.

Operating Costs

Powered

Zoom

Focus

Powered

Objective

Throw Ratio

Audio 2 x3W

> Cinch Video in Mini Jack in Ausgang

5 BNC Eingänge für RGBHV oder YUV Signal

S-Video in

Connections 2 xD-sub 15pin in

DVI Eingang VGA Ausgang

Serial Maus Control 9 Pin D-Sub

USB

Ceiling Mounting

Power


Yes 380W

282 x 150 x 429 mm (11,1"x5,9"x16,9") 18,15 L/dm3 Size WxHxD

Operating Noise

Weight 7,80 kg / 17,2 lbs. Keystone

Illumination



Frequenz H-sync: 15-94 kHz V-sync: 50-90 Hz

Foot-Lamberts 84 fL / max. 461 cm screen width

288 cd/m²

■ Remote control with laser pointer und mouse control

Overscan adjustable

■ Motorised keystone correction, digital keystone correction, interchangeable lenses available

as accessories

- Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

More Details

Features





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.