

Fuss FR 306B Pentathlon



Brief Introduction

Beta 2.5

Display Type

Ansi-Lumen
Contrast
Black Level
Offset

Resolution

Video Modes

Application

Light Source
Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting
Power

Size WxHxD

Operating Noise

The Whiteboard FR 306B pentathlon DLP projector from Fuss has 2600 Ansi lumens, a contrast of 3000:1 and a WXGA 1280 x 800 resolution. The model offers a microphone jack plug and 20W speakers, so no additional audio devices are required for presentations or training courses. Thanks to the brightness of 2600 Ansi lumens, a picture width of 518 cm is possible. In room light, the image should be max. 345 cm wide. The projector also offers a whiteboard function that makes training and presentation rooms interactive. It is no longer offered by the manufacturer Fuss.



1 x 0,65" DLP Chip

WXGA 16/10 Ti Digital Light Processing Chip

Projector
2600
3000:1 full on/off
0,8667 min. Lumen

Screen
1040 Lux (bei 200 cm Screen)
3000:1 full on/off
0,347 min. Lumen

WXGA 1280 x 800
1.024.000 Pixel

Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Whiteboard | Training and company presentations, as well as product presentations.

Medium screen width or rooms with little light, max. 100 lumens.

230W UHP Lamp

3000 h. 5000 h. in Eco Mode

-

-

No Zoom

-

0,54:1

2 x 20W

HDMI in
D-sub 15 pin in
USB in
Mikrofon in
RJ45 in

Yes

310W

463 x 150 x 355 mm (18,2"x5,9"x14") 24,65 L/dm³

-

9,50 kg / 20,94 lbs.

-

90%

-

97 fL / max. 518 cm screen width
332 cd/m²



- Eco Mode
- Lan network compatible.
- Short-throw projector
- Interactive Whiteboard function.

- Discontinued (EOL) // Last update of the data: 2023-08-04



HCinema

<https://www.projector-database.com/pro/fussfr306b-en.html>

More Details

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.