ITAC

Hitachi CP L500A





Brief Introduction

Display Type

Resolution

Video Modes

Light Source

Beta 2.5

The Hitachi CP L500A LCD projector has 300 Ansi lumens, a contrast of 200:1 and a VGA 640 x 480 resolution. The projector can illuminate images up to 151 cm wide thanks to its 300 Ansi lumens. In room light, however, the image width should ideally be less than 101 cm. It is no longer offered by the manufacturer Hitachi.

1 x 1,3 TFT Panel

VGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast

Projector 200:1 full on/off 1.5000 min. Lumen

300

០ ០ 200:1 full on/off ១ 0.493 min. Lumen

Black Level Offset

> VGA 640 x 480 307.200 Pixel NTSC, Pal, Secam

Stationary | Permanent installation in the training room and meeting room as well as the

Application conference room.

Very narrow picture width and rooms with very little light.

250W Metalldampf Lamp Articel Nr.: DT00031

2000 h. Light Life

10,67% / 0,35 € **Operating Costs**

Powered Focus

Zoom Powered 1,6

Objective F=3,0-3,8 f=46,5-74,4 mm

Throw Ratio 1,76-2,82:1

Audio 3W Mono

> 2 x D-sub 15pin 2 x Cinch Video in 4 x Cinch Stereo in 2 x S-Video in

Connections

Ceiling Mounting Power

Size WxHxD **Operating Noise** 370W

Weight Keystone Illumination

H-sync: 15,8-37,0 kHz Frequenz V-sync: 50-70 Hz

Foot-Lamberts 9 fL / max. 151 cm screen width

31 cd/m²


Features

DT00031 Lamp original

Optional Universal Remote original Fernb-uni-V3

Order here: https://www.hcinema.de/lampen/shop-en.php?id=1728

Status - Discontinued (EOL) // Last update of the data: 2023-08-04



Data

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.