Hitachi LP-WU3500



Brief Introduction Beta 2.5

Simulation

With the LP-WU3500, manufacturer Hitachi offers a stationary DLP LED projector with WUXGA 1920 x 1200 resolution and a contrast of 30000:1. The manufacturer specifies an LED service life of 20000 hours, which is over 13.7 years with a daily viewing time of 4 hours. With the lens shift function, the projector can be positioned very freely. 601 cm image width, the projector will be able to illuminate well. The projector can manage rooms with residual light with a smaller image width, we recommend a maximum of 401 cm. If the image width is not sufficient, the projector offers integrated edge blending software, which allows several projectors to project a large image together. A smartphone with MHL connection can be connected directly to the MHL/HDMI port and transmit a 1080p / 60 Hz image mirroring (screen mirroring) while the smartphone is being charged at the same time. The model built in 2016 is no longer offered by Hitachi. 1 x DLP Chip

Display Type

WUXGA 16/9 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level Lens shift

3500 30000:1 full on/off 0,1167 min. Lumen Vert.: +50% -0% Hori.: +/-4% დ1556 Lux (bei 200 cm Screen) 30000:1 full on/off 0,052 min. Lumen

Resolution

Video Modes

Application

Light Source

Light Life

WUXGA 1920 x 1200

2.304.000 Pixel

Pal, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Medium screen width or rooms with a little more ambient light, max. 200 lumens.

LED-Phosphor

Articel Nr.: HL03037 / R025H

20000 h.

Operating Costs

0,00 € LED

Focus

Manual

Zoom


Manual 1.64

Objective

Throw Ratio

1,3-2,30:1

Audio



2 x HDMI mit MHL in 1 x out D-sub 15pin in und out


Cinch Video in Cinch Stereo in

Mini Jack Audio in und out

USB in

RS232C Din 9 pin in RJ45 mit HDBaseT in

Connections



Ceiling Mounting Power

Yes 550W

Size WxHxD

396,2 x 132,1 x 454,7 mm (15,6"x5,2"x17,9") 23,73 L/dm³

Operating Noise

Weight 14,51 kg / 30,86 lbs.

Keystone Vert.: +/-30° Hori.: +/-30°

Illumination -

Frequenz H-sync: 15-106 kHz V-sync: 50-120 Hz

V 3/110. 00 120 112

Foot-Lamberts 145 fL / max. 601 cm screen width

497 cd/m²

■ Lens shift Funktion

- Eco Mode
- Warping
- 360° installable
- 24/7 continuous operation capable

- Picture-in-Picture
- Optional Wi-Fi network compatible.
- Lan network compatible.
- Crestron®-Software compatible.
- Dicom simulation

Remote control original HL03037 / R025H

Order here: https://www.hcinema.de/lampen/shop-en.php?id=fro9001836

2016 Discontinued (EOL) // Last update of the data: 2024-10-02

Created: 2016-10-27 13:38:14

Data

Status

Optional





More Details





Key: 150 cm Shift: 56 cm

Key: 150 cm

Key: 150 cm Shift: 8 cm

Key: 150 cm Shift: 8 cm

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.