Innoswell IS200-SVGA





Ansi-Lumen

Contrast

Display Type 3 x 0,55" LCD TFT Panel SVGA 4/3 Liquid Crystal Display

Black Level of

Offset -

SVGA 800 x 600

Resolution 480.000 Pixel

UXGA 1600 x 1200 compressed

Video Modes PAL, SECAM, NTSC,

Application Game-Portabel | Very portable, small-screen projections. Very narrow picture width and rooms with very little light.

Light Source -Light Life -Operating Costs -

porating ocoto

Focus Manual

Zoom No Zoom

Objective -

Throw Ratio -

Audio -

Connections Ceiling Mounting Power 110W

Size WxHxD 165 x 50 x 105 mm (6,5"x2"x4,1") 0,87 L/dm³

Operating Noise -

Weight 0,650 kg / 1,43 lbs.

Keystone -Illumination -

Frequenz -


Foot-Lamberts 5 fL / max. 107 cm screen width

17 cd/m²

Features -

Status Data

2011 Discontinued (EOL) // Last update of the data: 2023-08-04



ω50 Lux (bei 200 cm Screen) ο ο ο -

More Details



HCinema

https://www.projector-database.com/pro/innoswellledprojector-en.html

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.