## **IQI 7800**



**Brief Introduction** 

Beta 2.5

Display Type

Resolution

Application

Light Source

The IQI model 7800 is an LCOS projector with XGA 1024 x 768 resolution and a contrast of 300:1 according to Ansi 100:1. An image width of up to 337 cm is possible. However, the image should be smaller in room light. We recommend max. 225 cm. The projector is no longer sold by the manufacturer. Unfortunately, we can no longer offer replacement lamps for this model, neither originals nor replicas.

1 x 0,97 Lcos Panel

XGA 4/3 Liquid Crystal on Silicon (LCOS)

Offset -

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes Full NTSC, NTSC4.43, PAL, PAL-M, PAL-N,

Standard-Portabel | External training and company presentations, as well as product

presentations.

Small screen width, rooms with very little ambient light below 100 lumens.

150W UHP Lamp Articel Nr.: LMP1979

Light Life 2000 h.

Operating Costs -

Focus Manual

Zoom Manual 1,3

Objective -

Throw Ratio -

Audio 2 x 2,0W Stereo

1 D-sub 15pin

Connections 1 S-video

1 Composite video

Ceiling Mounting

Power 200W

Size WxHxD 252 x 182 x 356 mm (9,9"x7,2"x14") 16,33 L/dm<sup>3</sup>

Operating Noise 39dB

Weight 4,50 kg / 9,92 lbs.

Keystone -Illumination -

> H-sync: 50-85 kHz V-sync: 15-80 Hz Range max.: 140 MHz

Foot-Lamberts 46 fL / max. 337 cm screen width


158 cd/m<sup>2</sup>

Features

Status - Discontinued (EOL) // Last update of the data: 2023-08-04

Data

Frequenz



## More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.