Jingrui LP 800T





Brief Introduction

Beta 2.5

Ansi-Lumen

Contrast

Offset

The standard portable Jingrui LP 800T LCD projector has 1500 Ansi lumens, a contrast of 350:1 and an SVGA 800 x 600 resolution. 1500 Ansi lumens ensure that a picture width of 337 cm is also possible. However, if room light is available, the picture should be max. 225 cm wide. This model is no longer offered by Jingrui.

ω500 Lux (bei 200 cm Screen)

ត្តិ 350:1 [©] 1,441 min. Lumen

Display Type

3 x LCD TFT Panel SVGA 4/3 Liquid Crystal Display

1500

350:1 4,2857 min. Lumen

Black Level

SVGA 800 x 600

Resolution 480.000 Pixel XGA 1024 x 768 compressed

Video Modes PAL. SECAM. NTSC

Standard-Portabel | External training and company presentations, as well as product

presentations. Application

Small screen width, rooms with very little ambient light below 100 lumens.

Light Source Light Life

150W Lamp

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections Ceiling Mounting Yes 170W Power

Size WxHxD 270 x 115 x 360 mm (10,6"x4,5"x14,2") 11,18 L/dm³

Operating Noise

Weight Keystone Illumination

4,00 kg / 8,82 lbs. Vert.: +/-15°

96%

Frequenz


Foot-Lamberts 46 fL / max. 337 cm screen width

158 cd/m²

Features Status

Data

- Discontinued (EOL) // Last update of the data: 2023-08-04



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.