



DLA-VS2200ZG

Visualization Series D-ILA Projector
(Zoom Lens Version)

Low Cost of Ownership!

*Digital Smear Reduction
w/Black Frame Insertion*

*1920x1080
Native Resolution*

*High Dynamic Range
18,000:1 Native Contrast*



● Features

- 1920 x 1080 Native Resolution
- 3 Active Matrix, 0.7" Digital D-ILA Devices
- >18,000:1 Contrast Ratio
- Digital Smear Reduction via Black-frame Insertion
- 23ms Frame Delay
- 1080p60/50 Synchronous Operation
- 850 ANSI Lumens (minimum)
- 12-Bit Gamma Correction
- 7-Axis Color Management System
- 4000 hour, 250W Ultra High Pressure Lamp for Low Operating Cost
- Rugged Chassis for Motion-Base Applications
- 16 Step Aperture Control
- Sim Specific D-ILA Devices
- High Contrast IR output for stimulated NVG applications
- User Adjustable Gamma Tracking
- Long-life Wiregrid Polarizers
- Long-life Inorganic Optical Components
- Wide-Range Zoom Lens, 1.4-2.8:1 Throw Ratio
- $\pm 80\%$ V Offset, $\pm 34\%$ H Offset
- Flexible Orientation- ± 90 Deg. Pitch, ± 10 Deg. Roll
- 11x11 Matrix, 1/16 pixel Micro-Convergence Control
- Comprehensive LAN/RS232 Control Protocol
- Configuration Save/Restore Capability

Specifications

Image Device		3 D-ILA® devices (0.7 inches diagonal) >90% Aperture Ratio
Brightness		850 ANSI Lumens (minimum)
Resolution		1920x1080 Pixels (16:9 Aspect Ratio)
Contrast Ratio (Sequential)		18,000:1 minimum, 30,000:1 typical
Uniformity		Greater than 80%
Aperture		16 Steps (Lens and Lamp Aperture)
Gamma Control		Std 2.2 Gamma and 6 User adjustable Gamma presets
Color Management		7-Axis adjustable CMS
HDMI Input - Supported Formats		1920x1080 (EDID for 1080p60, 1080p50 only)
Low Latency Mode		1080p60/50
Latency		23ms w/1080p60 Input
Color Bit Depth		10-bit Input via HDMI 1.4a, 10-bit display
I/O Terminals		2 x HDMI v1.4a (locking HDMI connectors) LAN, RJ45 x 1 RS-232C, D-Sub 9 pin (male) x 1 Wired Remote (Mini) x 1
Remote Control		RS-232C/LAN Fully featured control protocol Wired/IR Remote Control
Standard Zoom Lens and Accessories	MNT-VS21-0	1.4-2.8:1 Zoom Lens (Remote Zoom and Focus) ± 80% Vertical Offset, ± 34% Horizontal Offset Fixed Mount Adapter for Zoom Lens (0% offset)
Lamp (user replaceable)	PK-L2313UP	230W Ultra High Pressure Type (170W Low, 230W High) 4000 hour nominal life to 50% brightness (Low Power Setting)
Power Requirement		AC 100V-240V, 50/60Hz
Power Consumption		360 Watts Maximum, 7W Standby
Noise Level (0-26°C, 32-79°F)		<35dB (A) at 39.4"/1m (3.3ft)
Operating Environment		Temperature range 5°C-35°C Humidity 20%-80% (non-condensing)
Operating Altitude		<1500 meters for guaranteed performance
Installation Orientation		Vertical ±90 degrees, Horizontal ±10 degrees
Dimensions (W x H x D)		17-15/16" x 7-1/16" x 18-5/8" (455 x 179 x 472mm)
Weight		34lbs, (14.6kg)
Supplied Accessories		Power Cord
Approvals	Safety	North America Europe
	EMI	North America
	Europe	
	Environmental	Australia Common North America Europe
		CSA C22.2 No.60950-1-03, UL60950-1 IEC60950-1 (EU) FCC part 15 Class B(US), ICES-003 Issue 4, 2004(CAN), EN61000-3-2, EN61000-3-3, EN61000-6-3 AS/NZS CISPR 22:2004 Class B RoHS Proposition 65 (US), Mercury Regulation WEEE New Battery directive
Warranty		Two Years Parts and Labor (per JVC Limited Warranty)



JVCKENWOOD

D-ILA is a trademark of JVCKENWOOD Corporation
E.&O.E., Design and specifications are subject to change without notice.
All brand names and product names are trademarks, registered trademarks, or trade names
of their respective holders.

Copyright 2015, JVCKENWOOD Corporation
All rights reserved

Rev 3.10.15