## I I Z X V I S I O Z







Brief Introduction
Beta 2.5

2650 Ansi lumens, a contrast of 1200:1 and an XGA 1024 x 768 resolution. 448 cm image width, the projector will be able to illuminate well. However, if room light is available, the image width should ideally not exceed 299 cm. This model is no longer offered by Lenovo.

Display Type

1 x 0,7" DLP Chip

XGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level Offset

Application

2650 / 1850 im Eco Mode 1200:1 full on/off 2,2083 min. Lumen -

XGA 1024 x 768 Resolution 786.432 Pixel

SXGA 1280 x 1024 compressed

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

Light Source 250W P-VIP Lamp Articel Nr.: 73P3191

Light Life 1500 h. 3000 h. in Eco Mode

Operating Costs -

Focus -

Zoom -

Objective -

Throw Ratio -

Audio -

DVi in

D-sub 15 pin in Cinch Video in

USB in

Ceiling Mounting

Connections

Power -

Size WxHxD 290 x 115 x 225 mm (11,4"x4,5"x8,9") 7,5 L/dm<sup>3</sup>

Operating Noise 35 / 34 dB in Eco Mode

Weight Keystone Illumination 3,40 kg / 7,5 lbs. Vert.: +/-15°

80%

Frequenz -

Lux:883 Lux
Room light max.:177 Lux
Candela pro m²:281 cd/m²
Foot-Lamberts:82 fL

4/3 screen width:200 cm
Screen:1 Gain

Foot-Lamberts 82 fL / max. 448 cm screen width

281 cd/m<sup>2</sup>

Features

■ Eco Mode

Status

Remote control with laser pointer

Data

2005 Discontinued (EOL) // Last update of the data: 2023-08-04

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.