


# Madrigal Imaging MP-D1

MADRIGAL IMAGING MP-D1



Display Type	 3 x D-ILA chip SXGA 4/3 Direct-Drive Image Light Amplification (D-ILA)
Ansi-Lumen	Projector - Lux (bei 200 cm Screen)
Contrast	Projector - Screen -
Black Level	Projector -
Offset	-
Resolution	SXGA+ 1365 x 1024 1.397.760 Pixel
Video Modes	HDTV, 480p, 720p, 1080i und weitere, NTSC, NTSC 4.43/ PAL / PAL-M / PAL-N , SECAM
Application	Stationary   Permanent installation in the training room and meeting room as well as the conference room. Very narrow picture width and rooms with very little light.
Light Source	420W Xenon Lamp
Light Life	-
Operating Costs	-
Focus	-
Zoom	-
Objective	-
Throw Ratio	-
Audio	2 x 1W
Connections	Y/C (S-Video) input (Mini DIN 4 pin)Composite Video (BNC)Component Video (Y, B -Y, R-Y) input on BNCRGBHV on BNCComputer in for RGB (DB15)RS232C terminal for external control
Ceiling Mounting	-
Power	660W
Size WxHxD	-
Operating Noise	-
Weight	-
Keystone	-
Illumination	-
Frequenz	H-sync: 15-82 kHz V-sync: 50-78 Hz
Foot-Lamberts	-
Features	-
Status	- Discontinued (EOL) // Last update of the data: 2023-08-04
Data	

More Details



<https://www.projector-database.com/pro/madrigalimagingmpd1-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.