



MC-X2500

Features

Display Technology	0.9 in. polysilicon active matrix TFT x 3
Native Resolution	XGA (1024 x 768)
Resolution Supported	VGA (640 x 480), SVGA (800 x 600), SXGA (1280 x 1024), Mac 13", Mac 16"
Brightness	2500 ANSI Lumens
Contrast Ratio	350:1
Computer Compatibility	IBM PC or compatibles, Apple Macintosh
Video Compatibility	NTSC 4.43, PAL, PAL-M, PAL-N, PAL-60, SECAM, HDTV (480i, 575i, 720p, 1080i)
Aspect Ratio	4:3, supports 5:4, 16:9
Number of Colors	16.7 million
Input Sources	Computer: 2RGB (HD-15), DVI, 2 Stereo audio (mini-jack) Video: Composite Video (RCA), S-Video (mini-DIN), Component Video (RCA), Audio (RCA x 2)
Output	RGB (HD-15), Audio (RCA)
Control	Mouse (PS/2, USB, Serial), RS-232
Keystone Correction	100% optical offset; Digital Keystone Correction: +/-15 degrees vertical, +/-5 degrees horizontal
Audio	2 x 1.0 watt stereo
Remote Control	Full-featured remote with mouse control and laser pointer



Technical

H-Sync Range	31 - 80 kHz
V-Sync Range	56 - 120 Hz
Horizontal Resolution	540 TV lines
Lamp (Life)	250 watt UHB (2000 hours)
Dimensions	14.2" (W) x 10.1" (L) x 4.2" (H) 360 mm (W) x 257 mm (L) x 106 mm (H)
Weight	9.9 lbs. (4.5 kg)
Power Consumption	410 watts
Power Requirements	100 - 120V/220 - 240V 50/60 Hz
Operating Temperature	32° to 95°F (0°-35°C)
On-Screen Menu Languages	English, French, Norwegian, Italian, German, Dutch, Spanish, Portugese
Audible Noise	<40dB (<36dB in whisper mode)
Approvals	CE, UL, cUL, TUV, FCC Class B
Security	Kensington lock compatible
Warranty	Three years limited parts and labor (90-day lamp warranty, 1-year temporary replacement program).

Standard Lens

Projection Lens	F: 1.74 - 2.08, f = 36.8 - 47.8 mm
Throw Ratio	2.0 to 2.56:1

Image Size (in.)			Throw Distance (ft.)	
Diagonal	Width	Height	Min.	Max.
40	32	24	5.3	6.8
60	48	36	8.0	10.2
80	64	48	10.7	13.7
100	80	60	13.3	17.1
120	96	72	16.0	20.5
150	120	90	20.0	25.6
200	160	120	26.7	34.1

Accessories

Spare Lamp (part no. MCX2500LAMP)	250 watt UHB (2000 hours)
Ceiling Mount	RPA-430

MCSi, Inc. Headquarters
4750 Hempstead Station Drive
Dayton, Ohio 45429
Tel. (800) 875-5211
Web Site: mcsinet.com
For information on other MCSi products: 800-516-0600

©2002 MCSi, Inc. All rights reserved. The MCSi & Radiant logo are registered trademarks of MCSi. All other trademarks contained in this document are the property of their respective owners. MCSi reserves the right to alter pricing, specifications and terms without notice at anytime.



04/01 D-VCG-1000-028

Portable projectors

MC-X2500



2500 lumens

True XGA 1024 x 768
resolution

H&V digital keystone
correction

Picture-in-picture

9.9 pounds

