

MEGAPOWER®

“ The First Name in Digital Projector “

Sunbeam®

**Short throw lens suitable
for a variety of classroom use**

- CMOS camera module built in projector
- Move the toolbar from left to right
- Computer Mouse Mode and Pen Mode
- The Color modes for sharp writing
- Mode Bold / Light for strokes
- The Left mouse and Right mouse for Computer
- Scroll Up / Down Mode
- 19 Languages: English, Vietnamese, French, Korean, Japanese, German, Thailand, Chinese, Russia,...
- Double-click Mode
- Thumb Mode
- Partial erase Mode
- Erase all operations Mode
- Recovery data Mode
- Save to computer Mode
- 2D Library
- Virtual Keyboard, ect.

Model: Sunbeam ML-678Wui



1

Easy to use

2

Easy to learn

3

Easy to energize your students



Optical	
Projection system	3LCD 0.63" BrightEra XGA Panel Technology CMOS Sensor Chip Technology
Brightness	3200 Ansi Lumens
Contrast ratio	2800:1
Resolution	Native: XGA (1024 x 768)
	Maximum: UXGA (1600 x 1200)
	Aperture ratio: 4:3 native / 16:9 compatible
Projecttion lens	14x pixels Zoom Digital , f=9.05mm, F/1.80,
Lamp	230W Lamp, 4000hrs
Fan Noise	32dB Normal; 27dB @ ECO
Image size	40" - 300" (Approx.100"@1.30M)
Throw ratio	0.51m ~ 2.70m
Signal	
Color system	NTSC / NTSC 4.43 / PAL (including PAL-M,N) / SECAM/ PAL60
Rate scan	Vertical 15 to 100kHz; Horizontal 48 to 120Hz
Video signals compatibility	480i/p, 576i/p, 720p, 1035i, 1080i
PC signals compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA
Keystone correction	Vertical $\pm 30^\circ$
Inputs terminals	RGB: Min D-sub 15pin x 1, DVI-I / HDMI x 1, S-Video x 1, Compisite Video (RCA x1), Audio: Mini jack x 2, RCA(L/R) x 1, Component Video (RCA x 3), HDMI
Outputs terminals	RGB: Min D-sub 15pin x 1, Audio: Mini jack x 1, USB Wireless Mouse Control
Projector Controls	RS-232C D-Sub 9pin x 1, RJ-45 (On/Off)
Language	19 Languages: English, French, Chinese, Vietnamese, Japanese, Korean, German, Thailand, Finland, Russia, Spain, Portugal, Italy, Sweden, Turkey, South Africa, Indonesia, Kuwait, Saudi.
Speaker	
	Stereo 1 x 8W
General	
Dimensions (WxHxD)	361.5 x 92 x 314.2 mm
Net Weight	3.6 Kg
Power requirement	AC 100 to 240 V, 50/60 Hz
Power consumption	Max. 280W, Standby 1W
Standard Accessories	
	Light Pen(37,5~65cm/121g) / E-pen(20cm/86g)
	Video Box / Remote control (Format Card) / Battery / Power AC Cable / VGA Cable / USB Wireless / HDMI Cable.
	Soft-Carrying Bag, Owner's Manual CD, Quick Guide.
Certification	
	ISO 9001:2008 / ISO 14001:2004 / UL / FCC Class B / CE / CB (IEC), RoHS,...

* Specifications subject to change without notice



MEGAPOWER IND. LTD.

Suite 903, Park Tower, 15 Austin Road, Tsimshatsui,
HongKong SAR in China.

Tel: 852-6216-0140 Fax: 852-8147-1900

E-mail: magapwr@netvigator.com

