MICROTEK

Digital Projector

CX7

Projection System	
• Native Resolution	1024 x 768 (XGA)
• Max Resolution	1280 x 1024 (SXGA)
• Display Type	0.7" DDR DLP x 1
• Brightness	2150 ANSI Lumens
• Lamp	250 watt
• Lamp Life	2000 hours
• Brightness Uniformity	80%
• Projection Lens	1: 1.2 manual zoom and focus; F2.4
• Displayable Colors	24 bit, 16.7million True Color
• Contrast Ratio	1200:1
• Aspect Ratio	4:3 & 16:9
• Projection Distance	4.92' - 32.81' (1.5m - 10m)
• Screen Size (diagonal)	30" - 300" (0.76m - 7.62m)
• Digital Keystone Correction	+/- 15°
• Audio	build-in 3w mono speaker
• Security Lock	Kensington Lock
• Remote Control Features	Wireless remote, Power, Auto image, Source select, Keystone, Menu, Enter, Volume (-/+), Arrow Key +/-/up/down, full OSD controls

Technical Specifications	
• Horizontal Scan Rate	15, 30 - 90KHz
• Vertical Refresh Rate	50 - 85Hz
• Installation Options	Front/Rear, Desktop/Ceiling
• Power Consumption	<340 Watts; <20 Watts Standby
• Power Supply Voltage	100 - 240VAC, 50/60Hz
• Operating Temperature	41°F - 95°F (5°C ~ 35°C)
• Dimensions (W x D x H)	285 x 220 x 85mm
• Weight	6.8 lbs (3.08 Kg)
• Audible Noise	35 dB (TYP.)

Connectivity	
• Computer Inputs	DVI-I x1; USB x1
• Video Inputs	S-Video x1; Component(thru DVI) x1
• Audio Inputs	mini jack x1
• Video Compatibility	NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM; SDTV: 480i (thru DVI-I); EDTV: 480p, 720p (thru DVI-I); HDTV: 1080i (thru DVI-I)

Included Accessories

Computer Cable, DVI-I to DB15 pin, Audio cable; S-Video cable, AC Power Cable, USB cable, Remote Control & batteries, Quick Setup Guide, User's Manual in multi-language as OSD (CD only), Compac Disc (inf.file), Carrying Case, Lens Cap

MICROTEK

www.microtek.com

Conference Projectors